





Hornet HP 3.5" Downlights




amerlux

Hornet HP 3.5" Downlight

Small in size, but big on performance, the Hornet HP Downlights deliver output equal to fixtures using the 20w ceramic metal halide source, but with better control, color, and performance. These LED downlights are destined to win you over.



Hornet HP 3.5" Downlights



Features:

- Downlight, Adjustable, Pinhole, Slot, & Shower
- Aperture: 3.5"
- Round or Square, Trim or Trimless, New Construction, or Remodeler
- Die-cast optical housing and trim
- Field replaceable LED module and driver
- Field changable beam spreads 15°-45°
- Lockable 0-30° tilt, 358° rotation
- Dimming capable (ELV, TRIAC, HILUME, 0-10v)
- Multi-Function options:
 - MF-EM: multi-function emergency
 - MF-NL: multi-function night light
- Ceiling types: Grid or Gyp (up to 1" thick)
- 50,000 hours of life (at 70% light output)

Specs:

- 17, 20w
- Up to 8,689 CBCP
- 2700K, 3000K, 3500K, 4000K
- 85 CRI (typ), 90 CRI (3000K only)
- 120-277v input
- Delivers up to 986lm
- For indoor use only



Downlight
(HDL-HP-RD)



Adjustable
(HDL-HP-RA)



Pinhole
(HDL-HP-RPA)



Slot
(HDL-HP-RPAS)



Shower
(HDL-HP-RPASHW)

Ordering Guide

	Housing Model	Wattage	Lamp Type	Driver	Voltage	Options
TRIM	HDL-HP-R HDL-HP-REM (remodeler)	17 20	LED	E - electronics	120 277	DIM-ELV - ELV dimming (120v only) DIM-TRIAC - Triac dimming (120v only) HILUME - Lutron Hi-Lume® dimming driver 0-10v - 0-10v dimming MF-EM - multi-function emergency driver MF-NL - multi-function night light driver
	TRIMLESS	HDL-HP-R-TL HDL-HP-REM-TL (remodeler)				

Example

HDL-HP-R-17-LED-E-120-DIM-ELV/HDL-HP-RD-MBW-FL-3000


Features



3.5" Aperture
Round & Square



Seamless die-cast trim
Round & Square



Die-cast trimless
Round & Square



Lockable aiming 0-45°




Quick Connect




Easy install clips
Up to 1" thick ceiling



Remodeler frame



Field changable beam
distributions



Multi-Function. MF-EM (auto)
MF-NL (instant switch)



Downlight
(HDL-HP-SD)



Adjustable
(HDL-HP-SA)



Pinhole
(HDL-HP-SPA)



Shower
(HDL-HP-SPASHW)

Trim Model

Aperture/Trim Finish

Beam Spread

Color Temp

**T
R
I
M**

HDL-HP-RD
HDL-HP-RA
HDL-HP-RPA
HDL-HP-RPAS
HDL-HP-RPASHW
HDL-HP-SD
HDL-HP-SA
HDL-HP-SPA
HDL-HP-SPASHW

Reflector with White Painted Flange
MBW - matte black
MWW - matte white
SLVW - matte silver

SP - spot, 15°
FL - flood, 28°
WF - wide flood, 45°
LS - linear spread, 60° x 10°

2700
3000
3500
4000
3000-90 (90CRI)

**T
R
I
M
L
E
S
S**

HDL-HP-RD-TL
HDL-HP-RA-TL
HDL-HP-RPA-TL
HDL-HP-RPAS-TL
HDL-HP-RPASHW-TL
HDL-HP-SD-TL
HDL-HP-SA-TL
HDL-HP-SPA-TL
HDL-HP-SPASHW-TL





5220 Shank Road, Pearland, TX 77581
T: 281.997.5400 | F: 281.997.5441
amerluxexterior.com

Headquarters
23 Daniel Road East, Fairfield, NJ 07004
T: 973.882.5010 | F: 973.882.2605
amerlux.com | amerluxexterior.com
© 2012 Amerlux, LLC

Oxidated Carpark 2nd Floor
No. 124 Donghuan Road, Donghuan Jie
Panyu, Guangzhou 511400 PRC
amerlux.com