

SPECIFICATIONS

- 120-277V input voltage, 50/60Hz
- Constant current at 700 mA
- Driver UL Class 2, power factor > .90
- Ambient operating temperature -40°C (-40°F) to +40°C (105°F)
- Estimated 50,000 hrs L70*
- Thermally protected LED array
- White powdercoated aluminum base and acrylic diffuser
- Ceiling mount only
- UL/CUL listed for damp location
- Standard pack qty: 8 (11" model) or 6 (14" model)

**DFC311
DFC314
DRUM**



**DFC321
DFC324
MUSHROOM**



ORDERING INFORMATION

Style Number	Source/Wattage	Color Temp	Body	Lens	Option
DFC311 = 11" Drum DFC321 = 11" Mushroom	L1300W = 6 CREE LED array (14W) 17W Power Input 1278 Lumens 75 Lumens per watt**	3000K CRI = 80 (TYP)	W = White	W = White	O = Occupancy Sensor
DFC314 = 14" Drum DFC324 = 14" Mushroom	L1700W = 8 CREE LED array (18W) 22W Power Input 1704 Lumens 77 Lumens per watt**				

L1300W LED REPLACEMENT PARTS	L1700W LED REPLACEMENT PARTS
L12W-DC-700-06-R = 6 CREE LED array	L18W-DC-700-08-R = 8 CREE LED array
IG1200-DMV-1 = LED driver	IG1800-DMV-1 = LED driver

* Data per LM79/LM80/TM21 available upon request
** Estimated from LED source



Your Commercial & Industrial Lighting SuperSource

Contact: sales@envoylighting.com • 215-512-7000