

## Wall luminaires with single-sided light output

**Housing:** Extruded and die cast aluminum. Mounts directly to a BEGA 537 box (provided). Die castings are marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy.

**Enclosure:** Tempered, clear glass, flush to the die casting to prevent water accumulation. Fully gasketed for weather tight operation using a 'U' channel molded silicone rubber gasket.

**Electrical:** 18W LED luminaire, 20.5 total system watts,  $-40^{\circ}\text{C}$  start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. Standard LED color temperature is 3000K with an 85 CRI. Available in 4000K (85 CRI); add suffix K4 to order.

**Notes:** LEDs supplied with luminaire. Due to the dynamic nature of LED technology, LED luminaire data on this sheet is subject to change at the discretion of BEGA-US. For the most current technical data, please refer to [www.bega-us.com](http://www.bega-us.com).



**Finish:** All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

**CSA** certified to U.S. and Canadian standards for wet locations. Protection class IP65

**Weight:** 7.3 lbs

**Luminaire Lumens:** 803  
Tested in accordance with LM-79-08

**Mounting options:**  
**547** Surface-mount wiring box



These luminaires mount over a custom BEGA recessed box. This box can be shipped ahead of the luminaire.

**Narrow beam upwards or downwards**

	Lamp	$\beta$	A	B	C	D	Wiring box*
	<b>6698LED.537*</b> 18W LED	19.5°	5 <sup>7</sup> / <sub>8</sub>	11 <sup>3</sup> / <sub>4</sub>	7 <sup>7</sup> / <sub>8</sub>	1 <sup>5</sup> / <sub>8</sub>	<b>537</b>

$\beta$  = Beam angle \*Small opening wiring box included.

Type:  
BEGA Product:  
Project:  
Voltage:  
Color:  
Options:  
Modified:

