







### AMEDICAN LIGHTING

BRIGHT IDEAS • INNOVATIVE PRODUCTS

### To Our Valued Customers,

American Lighting is committed to providing you with the highest quality residential and commercial lighting products and unsurpassed customer service in 2004 and beyond. All of our products are thoroughly tested at our manufacturing sites and by our in-house experts to ensure the highest performance standards. Superior customer service and innovative product designs set American Lighting apart from the competition. We are proud of our same day shipping policy for orders received by 2 p.m. (MST) and our low minimum order quantity requirements.

In order to serve our diverse customer base, from lighting showrooms to electrical distributors, designers and specifiers, American Lighting offers our customers the flexibility of placing orders from our catalog or custom orders direct from our factories. We are pleased to offer our esteemed customers a broad range of the finest quality products and the latest in technologies available in the lighting industry. American Lighting understands that innovation is a key strategic advantage for our customers and we are committed to unveiling new products on a continuous basis.

Thank you for choosing American Lighting. We greatly appreciate your business.

Sincerely,

David G. Wilkins President/CEO









Accent and Task Lighting Systems

### Illuminating beautiful glass art pieces and collectibles has never been easier!



Height: <sup>3</sup>/<sub>8</sub>", Depth: 10 <sup>1</sup>/<sub>2</sub>" Lengths: 16 <sup>1</sup>/<sub>2</sub>", 22 <sup>1</sup>/<sub>2</sub>" and 28 <sup>1</sup>/<sub>2</sub>"

- Bright, white light evenly distributed over entire shelf
- Very little heat, safe to use even in enclosed cabinets
- Includes Cold Cathode light bulb(s) 12,000 hours (average life)
- Economical, low energy consumption (3 watts per foot)
- Link multiple units together (up to 4)
- Single-side illumination
- Available in warm white 3200°K and cool white 6500°K
- · Power supply sold separately



Illumishelf used in tinted glass application.



| Item#                    | Description   |
|--------------------------|---|
| CCSL-18-CW<br>CCSL-18-WW | I6 <sup>1</sup> /2" Illumishelf 5 watts<br>includes inverter and "Y" connector        |
| CCSL-24-CW<br>CCSL-24-WW | 22 1/2" Illumishelf 6 watts<br>includes inverter and "Y" connector                    |
| CCSL-30-CW<br>CCSL-30-WW | 28 1/2" Illumishelf 8 watts includes inverter and "Y" connector                       |
| CC-PS3<br>CC-PS5         | 36 watt 3 amp plug-in power supply, I2V DC 60 watt 5 amp plug-in power supply, I2V DC |

The Illumishelf fits standard 18", 24" and 30" kitchen cabinets. Custom sizes are also available. Please call for assistance.

### Clear Channel

# Adjustable bright energy efficient light in a sleek Clear Channel.



Height: 1/2", Width: 1/2", Lengths: 13 3/4", 20 3/4" and 27 3/4"

- · Bright, warm white linear light
- Minimal heat generated for maximum safety
- Includes Cold Cathode light bulb 12,000 hours (average life)
- Low profile, 1/2" clear polycarbonate tube
- Remote ballast and transformer allow for simple installation
- Energy efficient cold cathode lamp uses 4 watts per foot
- Rotates 180°-swivel mounting hardware included
- Can be used in a variety of cabinet applications
- 12V power supply sold separately

| Item#              | Description  |
|--------------------|--|
| CC-14              | I3 <sup>3</sup> /4" Clear Channel, 3 watts<br>Includes inverter, "Y" connector and<br>3200° K lamp |
| CC-21              | 20 <sup>1</sup> /4" Clear Channel, 5 watts<br>Includes inverter, "Y" connector and<br>3200° K lamp |
| CC-28              | 27 <sup>3</sup> /8" Clear Channel, 7 watts<br>Includes inverter, "Y" connector and<br>3200° K lamp |
| CC-P\$3<br>CC-P\$5 | 36 watt 3 amp plug-in power supply, I2V DC 60 watt 5 amp plug-in power supply, I2V DC              |

Can be used for curio cabinets, stereo cabinets, bookcases, etc.



### **Brite-Line**

# A powerful, miniature light that will work end-to-end for a continuous band of light!



Height: 3/8", Width: 3/8", Lengths: 9 3/8", 17 3/8" and 25 3/8"

- Bright, cool white linear light
- Low profile, 3/8" square aluminum "U" channel
- Minimal heat generated for maximum safety
- Remote ballast and transformer allow for simple installation
- Energy efficient cold cathode lamp uses 4 watts per foot
- Includes Cold Cathode light bulb 12,000 hours (average life)
- · Install end-to-end for continuous light
- Double-sided tape included
- 12V power supply sold separately

| Item#            | Description   |
|------------------|---|
| BRL-8-CH         | 9 <sup>3</sup> /8" Brite-Line, 3 watts  |
| BRL-8-WH         | Includes inverter, "Y" connector and  |
| BRL-8-BR         | 6500°K lamp   |
| BRL-16-CH        | I7 <sup>3</sup> /8" Brite-Line, 5 watts   |
| BRL-16-WH        | Includes inverter, "Y" connector and  |
| BRL-16-BR        | 6500°K lamp   |
| BRL-24-CH        | 24 <sup>3</sup> /s" Brite-Line, 7 watts   |
| BRL-24-WH        | Includes inverter, "Y" connector and  |
| BRL-24-BR        | 6500°K lamp   |
| CC-PS3<br>CC-PS5 | 36 watt 3 amp plug-in power supply, I2V DC 60 watt 5 amp plug-in power supply, I2V DC |

Color: Chrome (CH), White (WH) and Bronze (BR). Custom sizes are also available. Please call for assistance.



### Xenon 120V Under Cabinet Light

### New! Cooler than Halogen, brighter than Fluorescent and easy to install.



- Bright white light ideal for countertops and workstations
- Includes 120V Xenon light bulbs 8,000 hours (average life)
- Low profile, only 1 1/4" high
- Frosted lens allows for even light distribution
- Convenient Hi/Low switch
- · Hinged lens makes lamp replacement safe and easy
- Link portable fixtures with optional 12" or 24" extension
- Direct wire box available (see accessories below)



| ltem#    | Hardwire Description                |
|----------|-------------------------------------|
| LXCIH-WH | Xenon Under Cabinet Fixture         |
| LXCIH-BS | I20V, 20 watts, 8" Length, I-Light  |
| LXCIH-BR | Hardwire                            |
| LXC2H-WH | Xenon Under Cabinet Fixture         |
| LXC2H-BS | I20V, 40 watts, I6" Length, 2-Light |
| LXC2H-BR | Hardwire                            |
| LXC3H-WH | Xenon Under Cabinet Fixture         |
| LXC3H-BS | I20V, 60 watts, 24" Length, 3-Light |
| LXC3H-BR | Hardwire                            |
| LXC4H-WH | Xenon Under Cabinet Fixture         |
| LXC4H-BS | I20V, 80 watts, 32" Length, 4-Light |
| LXC4H-BR | Hardwire                            |


| ltem#     | Portable Description  |
|-----------|---|
| LXCIP-WH  | Xenon Under Cabinet Fixture   |
| LXCIP-BS  | I20V, 20 watts, 8" Length, I-Light  |
| LXCIP-BR  | Plug-in   |
| LXC2P-WH  | Xenon Under Cabinet Fixture   |
| LXC2P-BS  | I20V, 40 watts, I6" Length, 2-Light   |
| LXC2P-BR  | Plug-in   |
| LXC3P-WH  | Xenon Under Cabinet Fixture   |
| LXC3P-BS  | I20V, 60 watts, 24" Length, 3-Light   |
| LXC3P-BR  | Plug-in   |
| LXC4P-WH  | Xenon Under Cabinet Fixture<br>120V, 80 watts, 32" Length, 4-Light<br>Plug-in |
| LXCP-20BP | I20V Xenon replacement bulb, 20 watts   |

Colors: Brushed Steel (BS) and Bronze (BR) with 6 foot black cord. White (WH) with 6 foot white cord.

| Universal Accessories for Portable Fixtures page 35 |         |           |
|---|---------|-----------|
|   |         |           |
| ALLVPTDIM   | ALHWBOX | ALSLHWBOX |

### Xenon 120V Puck Light

### Contemporary styling and bright white light.



**Patent Pending** 

Height: 1 1/4", Depth: 4 1/2" Lengths: 8", 16", 24" and 32"



**Hardwire Description** 

Halogen Under Cabinet Fixture

- Includes 120V Halogen light bulb(s) 2,500 hours (average life)
- Dimmable

Item#

LHC1H-WH

- Low-profile, only 1 1/4" high
- Contemporary style in three great finishes
- Convenient Hi/Low switch
- · Frosted lens softens and diffuses light
- Hinged lens cover for easy lamp replacement
- Link portable fixtures with optional 12" or 24" extensions
- Direct wire box available (see accessories below)

| LHC1H-BS<br>LHC1H-BR             | I20V, 35 watts, 8" Length, I-Light<br>Hardwire   |
|----------------------------------|--|
| LHC2H-WH<br>LHC2H-BS<br>LHC2H-BR | Halogen Under Cabinet Fixture<br>I20V, 70 watts, I6" Length, 2-Light<br>Hardwire   |
| LHC3H-WH<br>LHC3H-BS<br>LHC3H-BR | Halogen Under Cabinet Fixture<br>120V, 105 watts, 24" Length, 3-Light<br>Hardwire  |
| LHC4H-WH<br>LHC4H-BS<br>LHC4H-BR | Halogen Under Cabinet Fixture<br>120V, 140 watts, 32" Length, 4-Light<br>Hardwire  |
|                                  |  |
| Item#                            | Portable Description   |
| LHCIP-WH                         | Portable Description  Halogen Under Cabinet Fixture 120V, 35 watts, 8" Length, 1-Light Plug-in   |
|                                  | Halogen Under Cabinet Fixture<br>120V, 35 watts, 8" Length, 1-Light  |
| LHCIP-WH                         | Halogen Under Cabinet Fixture 120V, 35 watts, 8" Length, 1-Light Plug-in Halogen Under Cabinet Fixture 120V, 70 watts, 16" Length, 2-Light |

Colors: Brushed Steel (BS) and Bronze (BR) with 6 foot black cord. White (WH) with 6 foot white cord.

| Universal Accessories for Portable Fixtures page 35 |         |           |
|---|---------|-----------|
| <b>%</b> .  | 1       |           |
| ALLVPTDIM   | ALHWBOX | ALSLHWBOX |

## Bright white light without the need for a transformer.





Surface mount height: 1 3/8" CUL) US

Recess mount height: 1/2", Diameter: 2 5/8"

- · Versatile, no transformer needed
- Does not emit damaging ultraviolet (UV) rays
- Dimmable
- Includes 120V Xenon light bulb(s) 8,000 hours (average life)
- · Lasts three times longer than Halogen
- · Frosted twist lock lens reduces glare
- Twist-off lens cover makes lamp replacement easy
- Ventilation pins provide airflow between puck light and mounting surface
- Can be used in a variety of cabinet applications
- Link up to ten units together
- Direct wire box available (see accessories below)

| ltem#                      | Description  |
|----------------------------|--|
| LVPX20WH-B                 | Xenon I20V Puck Light - Boxed  |
| LVPX20BK-B                 | Includes (1) 20 watt Xenon bulb  |
| LVPX20CH-B                 | Power cord not included  |
| LVPX20GD-B                 | Requires ALLVPPC6  |
| LVPX20WH                   | Xenon 120V Puck Light - Blister Pack   |
| LVPX20BK                   | Includes 6 foot power cord with  |
| LVPX20CH                   | slide-on plug and (1) 20 watt Xenon  |
| LVPX20GD                   | bulb   |
| LVPX40WH                   | Xenon I20V Two Puck Kit - Blister Pack   |
| LVPX40BK                   | Includes 6 foot power cord with  |
| LVPX40CH                   | slide-on plug, (1) I2" extension and   |
| LVPX40GD                   | (2) 20 watt Xenon bulbs  |
| LVPX80WH                   | Xenon 120V Four Puck Kit - Blister Pack  |
| LVPX80BK                   | Includes 6 foot power cord with  |
| LVPX80CH                   | slide-on plug, (3) 12" extensions and  |
| LVPX80GD                   | (4) 20 watt Xenon bulbs  |
| ALLVPPC6-B<br>ALLVPPC6WH-B | 6 foot power cord – Boxed<br>With slide-on plug and roll switch<br>Black or White        |
| ALLVPPC6<br>ALLVPPC6WH     | 6 foot power cord – Blister Pack<br>With slide-on plug and roll switch<br>Black or White |
| LVPX20B                    | I20V Xenon replacement bulb,<br>20 watts, two per Blister Pack                           |

Colors: Chrome (CH), Gold (GD) and Black (BK) with 6 foot black cord. White (WH) with 6 foot white cord.

| Universal Accessories for Portable Fixtures page 35 |         |           |          |                |
|---|---------|-----------|----------|----------------|
|   |         |           | 5        | ~              |
| ALLVPTDIM   | ALHWBOX | ALSLHWBOX | ALLVPPC6 | ALLVPEX12 & 24 |

### Xenon 12V Puck Light

# Halogen lighting without the need for a transformer.





Surface mount height: 1 3/8" CUL) US

Recess mount height: 1/2", Diameter: 2 5/8"

- Easy to install just plug them in!
- Dimmable
- Includes 120V Halogen light bulb 2,500 hours (average life)
- Frosted twist-lock lens reduces glare
- Ventilation pins provide airflow between puck light and mounting surface
- Can be used in a variety of cabinet applications
- Link up to ten units together
- Direct wire boxes available (see accessories below)

| Item#  | Description  |
|--|--|
| ALLVP20WH-B<br>ALLVP20BK-B<br>ALLVP20CH-B<br>ALLVP20GD-B | I20V Halogen Puck Light - Boxed<br>Includes (1) 20 watt Halogen bulb<br>Power cord not included<br>Requires ALLVPPC6       |
| ALLVP20WH<br>ALLVP20BK<br>ALLVP20CH<br>ALLVP20GD         | I20V Halogen Puck Light - Blister Pack<br>Includes 6 foot power cord with<br>slide-on plug and (1) 20 watt<br>Halogen bulb |
| ALLVPTDIM  | Touch pad dimmer, I20V   |
| ALLVPPC6-B<br>ALLVPPC6WH-B                               | 6 foot power cord – Boxed<br>With slide-on plug and roll switch<br>Black or White  |
| ALLVPPC6<br>ALLVPPC6WH                                   | 6 foot power cord – Blister Pack<br>With slide-on plug and roll switch<br>Black or White                                   |
| ALLVP20B   | I20V Halogen replacement bulb<br>20 watts, two per Blister Pack  |

Colors: Chrome (CH), Gold (GD) and Black (BK) with 6 foot black cord. White (WH) with 6 foot white cord.

# Universal Accessories for Portable Fixtures page 35

ALSLHWBOX

# Cooler than Halogen and longer lamp life makes this a perfect solution.





Surface mount height: 1 3/8" CUL US
Recess mount height: 1/2", Diameter: 2 5/8"

- Does not emit damaging ultraviolet (UV) rays
- Dimmable
- Includes 12V Xenon light bulb(s) 10,000 hours (average life)
- Lasts four times longer than Halogen
- 48" Lead wire with screw-down terminal block
- Frosted, glare-free, twist-lock lens
- Ventilation pins provide airflow between puck light and mounting surface
- Can be used in a variety of cabinet applications

| Item#  | Description  |
|--|--|
| ALPX20WH-B<br>ALPX20BK-B<br>ALPX20GD-B<br>ALPX20CH-B | Xenon Puck Light – Boxed<br>Includes (1) 20 watt, I2V Xenon bulb   |
| ALPX20WH<br>ALPX20BK<br>ALPX20GD<br>ALPX20CH         | Xenon Puck Light – Blister Pack<br>Includes (1) 20 watt, I2V Xenon bulb  |
| ALPX40WH<br>ALPX40BK<br>ALPX40GD<br>ALPX40CH         | Xenon 2-Puck Light Kit – Blister Pack<br>Includes 2 puck lights, (2) 20 watt, 12V<br>Xenon bulbs and 60 watt transformer |
| ALPX60WH<br>ALPX60BK<br>ALPX60GD<br>ALPX60CH         | Xenon 3-Puck Light Kit – Blister Pack<br>Includes 3 puck lights, (3) 20 watt, 12V<br>Xenon bulbs and 60 watt transformer |
| ALX IOBX   | I2V Xenon replacement bulbs I0 watts, two per Blister Pack   |
| ALX20BP  | I2V Xenon replacement bulbs<br>20 watts, two per Blister Pack  |

Colors: Chrome (CH), Gold (GD) and Black (BK) with black lead wire. White (WH) with white lead wire. Transformer sold separately.
\*See pages 27-28 for appropriate transformers.

| System Components |        |         |          |         |
|-------------------|--------|---------|----------|---------|
|                   | Page 1 | 7       | Î        |         |
| ALTR60PI          | ALTR60 | ALTPDIM | ALPX20BP | ALTR120 |

### Halogen 12V Puck Light

# Halogen Puck Lights are an excellent choice when a small, powerful light is required.



Surface mount height: 1 3/8" CULUS

Recess mount height: 1/2", Diameter: 2 5/8"

- Dimmable
- Includes 12V Halogen light bulb 2,500 hours (average life)
- 48" Lead wire with screw down terminal block
- Frosted, glare-free, twist-lock lens
- Ventilation pins provide airflow between puck light and mounting surface
- Can be used in a variety of cabinet applications

| Item#                               | Description   |
|-------------------------------------|---|
| ALP20WH-B<br>ALP20BK-B<br>ALP20GD-B | Halogen Puck Light – Boxed Only<br>Includes (1) 20 watt, I2V Halogen bulb |
| ALTPDIM                             | 3-Level Touch Dimmer, 300 watts   |
| AL20B                               | I2V Halogen replacement bulb, 20 watts<br>One per Blister Pack            |

Colors: Gold (GD) and Black (BK) with black lead wire. White (WH) with white lead wire. Transformer sold separately.

\*See pages 27-28 for appropriate transformers.



Illuminated Counter Top Displays are available for all Under Cabinet Products. Choose one with any \$500.00 purchase.

# System Components ALTR60PI ALTR60 ALTPDIM ALPX20BP ALTR120

### Fluorescent Task Light

### New, versatile, and energy efficient. Just plug-in!






Surface mount height: 1 1/4" GULUS

Recess mount height: 5/16", Width: 2 9/16", Length: 67/8"

- Energy efficient only 4 watts!
- Low profile fixture fits in tight spaces
- Includes 120VT5 Fluorescent light bulb 8,000 hours (average life)
- Link up to ten units together
- Prismatic, glare-free lens
- Can be used in a variety of cabinet applications

| Item#     | Description                              |
|-----------|--|
| ALFLP20WH | Fluorescent Puck Light—Retail Pack       |
| ALFLP20BK | Includes 6 foot power cord with          |
| ALFLP20CH | slide-on plug, roll switch and 4 watt T5 |
| ALFLP20GD | Fluorescent bulb                         |

Colors: Chrome (CH), Gold (GD) and Black (BK) with 6 foot black cord. White (WH) with 6 foot white cord.



| Universal Accessories for Portable Fixtures page 35 |           |           |         |
|---|-----------|-----------|---------|
| 6   | R         |           |         |
| ALLVPEX12   | ALLVPEX24 | ALSLHWBOX | ALHWBOX |

### **Ultra-Thin Fluorescent Light**

# Energy efficient, cool burning light in a very slim package.



Height: 1 1/4", Width: 5/8" CUL US Lengths: 15" and 21"

- Brighter workspace lighting from a smaller fixture
- Tri-Phosphor coating provides warm light (3100°K)
- · Touch On/Off switch with LED indicator
- · Instant "On"
- Includes T4 Fluorescent light bulb 10,000 hours (average life)
- Link up to ten units together with in-line connector (included) or linkable connectors (see below)
- · Durable lens cover protects light bulb
- Electronic ballast eliminates flicker and hum
- Direct wire box available (see accessories below)
- 6' power cord included

| Item #     | Description                          |  |
|------------|--------------------------------------|--|
| ALFLT4I5   | Ultra-Thin Fluorescent Light         |  |
| ALFLT42I   | 15" fixture, 8 watts or 21" fixture, |  |
|            | 16 watts, White, Blister Pack        |  |
| ALLVPEX 12 | I2" and 24" Extension cables         |  |
| ALLVPEX24  | link up to ten lights together       |  |
| ALHWBOX    | Direct Wire Box, (2) I20V            |  |
| ALHWBOX-WH | outlets & (2) on/off switches        |  |
| ALFL8B     | Tri-Phosphor T4 replacement bulb     |  |
| ALFL 16B   | 8 watts and 16 watts                 |  |
|            |                                      |  |

# System Components ALFLES & ALFLIGS ALLVPEX12 ALLVPEX24 ALHWBOX

### Adjustable Fluorescent Light

### Direct the light exactly where you need it!



Height: 1 1/4", Depth: 4 1/2" CL

- Fixture rotates 180°
- · Tri-Phosphor coating provides warm, white light
- Includes T4 Fluorescent light bulb 10,000 hours (average life)
- Link up to ten units together, 6" extension included
- · Mirrored reflector housing efficiently distributes light
- Convenient On/Off switch
- Optional 12"/24" extensions and direct wire boxes available (see accessories below)
- · Electronic ballast eliminates flicker and hum
- Instant "On"
- 6' power cord included

| Item#                        | Description  |  |
|------------------------------|--|--|
| ALFLSW815<br>ALFLSW1621      | Adjustable Fluorescent Light<br>8 watt, 15" fixture, white or<br>16 watt, 21" fixture, white |  |
| ALLVPEX I2WH<br>ALLVPEX 24WH | Linkable Connector – use like an extension cord, 12" or 24", White                           |  |
| ALFL8B<br>ALFL16B            | Tri-Phosphor T4 replacement bulb<br>8 watts or 16 watts                                      |  |



Illuminated Retail Displays are available for all Under Cabinet Products. Display includes 2 foot by 5 foot black grid with mounting base and display hooks. Available with any purchase of \$750.00 or more.





### Flexible, low voltage, versatile system with limitless applications!



### Lamp holder with bulb stands I" high



- Pre-assembled lamp holders on 12 gauge SPT-2 cable
- 3", 4" and 6" spacing (on-center) for maximum flexibility
- Mounting track available for straight-line installations
- Easily convert to spotlight with socket adapter for MR11 and MR16 bulbs, 20 watts max
- 100 foot spools are available and can be cut to length
- Lamp holders feature a built in reflector for maximum light output
- · Dimmable, 12V and 24V
- Perfect for coves, soffits, under cabinets, work stations and accent lighting applications

| Item#                         | Description                               |  |
|-------------------------------|---|--|
| FSL-3                         | Pre-assembled Linear Accent Series        |  |
| FSL-4                         | 3", 4" and 6" spacing on-center available |  |
| FSL-6                         | Custom cut or 100 foot spools             |  |
| FSL-TRK-3                     | 3 foot White mounting track               |  |
| FSL-TRK-4                     | 4 foot White mounting track               |  |
| FSL-END                       | End Cap, White                            |  |
| FSL-BLK                       | Connector Block, 2-wire, 12-gauge         |  |
| FSL-BOX                       | Junction box for FSL-BLK                  |  |
| FSL-SOCKET Replacement Socket |   |  |
| FSL-CLIP                      | -CLIP Saddle mounting clip                |  |
| FSL-COVER                     | Lens Cover, use with 5 watt bulb only     |  |
| FSL-CABLE                     | Replacement Cable, 12-gauge, White        |  |
| FSL-5-12/24                   | 5 watts, I2V or 24V bulb, Clear           |  |
| FSL-10-12/24                  | 10 watts, 12V or 24V bulb, Clear          |  |
| FSL-5F-12/24                  | 5 watts, I2V or 24V bulb, Frosted         |  |
| FSL-10F-12/24                 | 10 watts, 12V or 24V bulb, Frosted        |  |
| MR-II/I6A*                    | Swivel Socket attachment                  |  |
|                               | for MR II's                               |  |
| MR-II-I2*                     | MR II Bulb for Linear Accent Series       |  |
| MR-II-24*                     | 12V or 24V, 20 watts                      |  |
| * MD ( ( )                    | 1.1 . 1 . 1 . 1 MB (1/1/4)                |  |

<sup>\*</sup> MRII lamps are sold separately and require MR-II/I6A adapters.



### Linear Accent Kits CUL) US

| Item#     | Description  |  |  |
|-----------|--|--|--|
| FSLK-2    | 2 foot kit 4" o/c with 60 watt transformer                   |  |  |
| FSLK-4    | 4 foot kit 4" o/c with 80 watt transformer                   |  |  |
| FSLK-6    | 6 foot kit 4" o/c with 105 watt transformer                  |  |  |
| FSLK-I0   | I0 foot kit 4" o/c with I50 watt transformer                 |  |  |
| FSL-TRK-3 | 3' White mounting track                                      |  |  |
| FSLK-BU   | BU (2) 5 watt 12V Xenon lamps Blister Pack                   |  |  |
| FSLK-EX   | Extension Kit – 36" with two connector blocks - Blister Pack |  |  |
| FSLK-CV   | Clear Lens Covers-six per Blister Pack                       |  |  |

All kits include 5 watt bulbs on 12 gauge wire, 4" spacing on-center (o/c), a transformer and mounting accessories. 12V Xenon bulbs have an average life of 20,000 hours.



Maximum Single Run Distance

| 5 watt | 3"  | 4"  | 6"  |
|--------|-----|-----|-----|
| 12 V   | 6'  | 16' | 24' |
| 24V    | 24' | 32' | 48' |

240 watts maximum for 12V run. 480 watts maximum for 24V run. \*See pages 27-28 for appropriate transformers.

### Versatile, elegant accent lighting.



### Socket dimensions: 1/2" Length x 2/3" Height



- Low profile design socket with bulb stands 11/4" tall
- Pre-assembled lamp holders on 14 gauge SPT-2 Wire
- 4" lamp spacing on-center
- 330 foot spools are available and can be cut to length
- Use either Incandescent or Xenon bulbs
- Maximum run for 24V is 300 watts and for 12V is 150 watts

| Item#   | Description  |  |
|---|--|--|
| X-COVE  | X-Cove Light 4" spacing  |  |
| X-CLIP<br>X-END<br>FSL-BLK<br>FSL-BOX<br>FSL-WIRE | Mounting Clips End Cap Connector Block Junction Box for FSL-BLK Lead Wire, 12 gauge SPT-2, White |  |
| C-CAP-COLOR                                       | Plastic Cap - Clear, Red, Green, Blue,<br>Yellow. Cap can be only used with<br>3 watt lamp       |  |
| BX-5-12<br>BX-5-24                                | I2V Xenon bulb, 5 watts<br>24V Xenon bulb, 5 watts<br>II,000 hours (average life)                |  |
| BC-3-12<br>BC-3-24                                | I2V Incandescent Bulb, 3 watts<br>24V Incandescent Bulb, 3 watts<br>2,000 hours (average life)   |  |

<sup>\*</sup>See pages 27-28 for appropriate transformers.

### Flexible, low voltage system great for highlighting architectural elements.



### Width: 1/2", Height: 3/4" with bulb



- Includes 24V Incandescent light bulb(s) 20,000 hours (average life)
- Parallel wiring if one bulb burns out, the rest stay lit
- 2", 3" and 4" on center spacing available
- Field cuttable for maximum flexibility
- Lightweight easy to attach
- For indoor use only
- Maximum Run Distance 200 bulbs: 2" 33 feet; 3" 50 feet; 4" - 66 feet

| Item#                                 | Description                           |  |
|---------------------------------------|---------------------------------------|--|
| TL-2-2                                | Tape Light, 2 wire                    |  |
| TL-2-3                                | 2", 3" and 4" on center               |  |
| TL-2-4                                | 24V, Clear tape and socket            |  |
| TL-BULB-24                            | Replacement bulb, 24V, .96 watts 40ma |  |
| TL-CAP-I                              | Colored Caps; Red, Green, Blue,       |  |
| TL-CAP-O                              | Yellow, Clear; Indoor and Outdoor     |  |
| TL-CL-I                               | Bulb Mounting clip                    |  |
| TL-RR                                 | Tape Light retainer ring              |  |
| TL-END                                | End Cap, Clear                        |  |
| TL-CONBL2 Connector Block             |                                       |  |
| Pull Consideration 2.4V 07 mate 40 ma |                                       |  |

Bulb Specifications: 24V, .96 watt, 40ma Maximum Run: 200 Bulbs

| System Components |         |        |        |       |  |
|-------------------|---------|--------|--------|-------|--|
|                   |         |        |        |       |  |
| FSL-BLK           | FSL-BOX | BX5-12 | X-CLIP | X-END |  |

|            | System Components |         |        |           |
|------------|-------------------|---------|--------|-----------|
|            |                   | cal-300 |        |           |
| TL-BULB-24 | TL-CAP            | TL-CL-I | TL-END | TL-CONBL2 |

### **Chasing Rope Light**

Flexible, versatile, long-lasting, colorful, dimmable and easy to use.



- Colors: Clear, Frosted, Red, Green, Blue, Yellow, Amber, Purple and Pink
- Available in bulk reels, kits and custom cut to size
- 25,000 hours (average life)
- Crushproof to 240 PSI
- Field cuttable: 12V 2"; 24V 4"; 120V 18"
- Maximum Run Distance: 120V 150 feet; 12V 16 feet; 24V - 32 feet
- Energy consumption: 5.5 watts per foot
- 3/8" and 1/2" diameter sizes available
- Dimmable


| Item#            | Description                 |
|------------------|-----------------------------|
| DL/MDL-COLOR     | Bulk Rope Light*            |
| DL/MDL-CONKIT-6  | Bulk Connector Kit          |
| DL/MDL-PWR       | Power Connector             |
| DL/MDL-END       | End Cap                     |
| DL/MDL-SPL       | Splice Connector            |
| DL/MDL-EXT-2-KIT | 2 foot Extension Kit        |
| DL/MDL-CLIP      | "U" shaped mounting clip    |
| DL/MDL-TRACK-4   | 4 foot Clear mounting track |
|                  |                             |

\*DL = 1/2" Rope Light, MDL = 3/8" Rope Light, 150' reels Bulb Specifications: 1" spacing, 6.5V, .5 watts, 70MA Rope Light is available in 12V, 24V and 120V. Power cords are available in lengths of 2 feet, 6 feet and 15 feet.

### Rope Light Kits (I)

| Item#    | Description                           |
|----------|---------------------------------------|
| LR-CL-6  | Rope Light Kits - 1/2" in diameter    |
| LR-CL-9  | Includes power cord,                  |
| LR-CL-I5 | connector kit and mounting            |
| LR-CL-30 | accessories. 6 feet, 9 feet, 15 feet, |
| LR-CL-45 | 30 feet and 45 feet lengths available |

<sup>\*</sup>Rope Light Kits are available in clear only.



### Bright, colorful and attention grabbing! Nothing catches your eye like moving lights.



- Colors: Clear, Frosted, Red, Green, Blue, Yellow, Amber, Purple and Pink
- Bi-Colors: Red/Clear, Red/Yellow, Red/Green, Yellow/Green
- 25,000 hours (average life)
- · Crushproof to 240 PSI
- Maximum run distance: 150 feet
- Energy consumption: 5.5 watts per foot
- Field cuttable every 36" for maximum flexibility
- 1/2" diameter

| Item#                  | Description   |
|------------------------|---|
| DLCH-COLOR<br>DLCH-PC6 | Bulk Chasing Rope Light* Bulk 5 feet power cord for "all-on"                          |
| DLCH-PWR<br>DL-END     | Power Connector<br>End Cap  |
| DLCH-SPL               | Splice Connector  |
| DLCH-T                 | "T" Connector to combine three sections   |
| DLCH-Y                 | "Y" connector with power cord to power two runs of rope light                         |
| DLCH-EX<br>DLCH-EC     | 10 foot extension to link two sections<br>10 foot extension, rope to controller       |
| DLCH-30<br>DLCH-202    | Controller, chases up to 30 feet of rope<br>Controller, chases up to 150 feet of rope |
| DL-CLIP<br>DL-COND     | "U" shaped mounting clip<br>"P" shaped conduit clip                                   |
| DL-TRACK-4             | 4 foot Clear mounting track   |
| *Dulb anasification    | a. I" amasina ( EV Esuatta 70ma   |

<sup>\*</sup>Bulb specifications: I" spacing, 6.5V, .5 watts, 70ma.



### Clip Light

# A low profile light that provides safety and style for all types of floor surfaces.



### ST-1003 Tube Height: 1/4", Width: 5/16"

- Perfect for steps, aisles, pathways or enhancing architectural detail
- Tube colors: Clear, Red, Green, Blue, Amber and Smoke
- 40,000 hours (average life)
- Premium quality bulbs wired in series, 12V or 24V
- Tube length: Clear 24 feet, all other colors 20 feet
- Maximum run distance: 120 lamps for 24V and 72 lamps for 12V
- Bulb specifications: .5 watts, 70ma
- Bulb spacings: 1", 2", 3", 4", 6" and 12"
- Rated for indoor & outdoor use

| Item#           | Description                             |
|-----------------|---|
| ST-1003         | 1/4" x 5/16" polycarbonate tube         |
|                 | with custom lamp spacing                |
| STMC-I          | "U" Clip for 1003                       |
| STBP-I          | Bi-pin in-line connector                |
| STBP-2          | Bi-pin corner connector                 |
| CE-BRONZE       | Carpet to Edge Extrusion                |
| CE-NATURAL      | Use to abut a wall or a step riser      |
| CF-BRONZE       | Carpet to Floor Extrusion               |
| CF-NATURAL      | Helps indicate change in floor surface  |
| CS-BRONZE       | Carpeted Step Extrusion – Adds a        |
| CS-NATURAL      | safety factor and prevents wear         |
|                 | at the bullnose                         |
| BS-BRONZE       | Bare Step Extrusion – For               |
| BS-NATURAL      | installations on wood, tile or concrete |
| PU-EXTRUSION    | Clear Polycarbonate "U" Channel         |
| PT/PC-EXTRUSION | PVC channel with a removable cap        |
|                 | for concrete application                |

<sup>\*</sup>See pages 27-28 for appropriate transformers.



# A safe low voltage alternative source for year round tree lighting and building outlines



### Dimensions: 1/2" Length x 5/8" Width x 7/8" Height w/lamp



- · Sockets mounted on 18 gauge wire rated for outdoor use
- Includes 12V or 24V incandescent bulb(s) 20,000 hours (averagae life)
- Parallel wiring if one bulb burns out the rest stay lit
- Field cuttable
- · Dark green wire and socket


| Item#   | Description  |
|---|--|
| CL-2-GR-I2/24<br>CL-6-GR-I2/24<br>CL-9-GR-I2/24<br>CL-I2-GR-I2/24 | Clip Light, 12V and 24V 18 gauge wire.<br>Bulb spacing: 2", 6", 9" and 12" on-center<br>Dark green wire and socket                       |
| CL-SOCK-COLOR<br>CL-WIRE-COLOR<br>CL-BULB-I2/24                   | Socket Bulb: Clear, Green, Black<br>18 gauge stranded wire<br>Black, Green and White<br>Replacement bulbs, 12V/.5 watt and<br>24V/I watt |
| CL-RR   | Retainer ring for through-mounting   |
| CL-CAP-I<br>CL-CAP-O  | Colored Caps: Red, Green, Blue<br>Yellow and Clear;<br>Indoor and Outdoor use  |

Wattage: 12V bulbs use .5 watt each and 24V use .96 watt each. Maximum Run: 80 bulbs for 12V; 175 bulbs for 24V.

|         | System Components |        |           |
|---------|-------------------|--------|-----------|
|         |                   |        | *         |
| CL-BULB | CL-CAD-I/CL-CAD-O | TL-END | TL-CONBL2 |

### **Festoon Light String**

### Low maintenance lighting system designed for installations where lamp changing is difficult.



### Diameter: 2 1/2" Polycorbonate Globes



- · Custom manufactured to your exact specifications
- · A complete system includes cable, sockets, bulbs, and globes
- · Safe, multipurpose energy saving system
- Clear or colored polycarbonate globes available
- · Waterproof and resistant to vibration
- · Parallel wiring means loss of one bulb does not affect remaining bulbs
- · Ideal for buildings, bridges and other structures
- Halogen 3,000 hours (average life) or Xenon 20,000 hours (average life)

| Item#                           | Description   |
|---------------------------------|---|
| LFS-12-5                        | Festoon Light Socket with Globe and I2V Halogen bulb, 5 watts I2 gauge wire sold separately*        |
| LFS-24-5<br>LFS-24-8.5          | Festoon Light Socket with Globe<br>and 24V Xenon bulb, 5 watts, 8.5<br>watts or 10 watts            |
| LFS-24-10                       | 12 gauge wire sold separately*  |
| LFS-CABLE<br>LFS-CC             | Festoon Light String Cable, 12 gauge<br>Cable Clip with nail, Black                                 |
| LFS-BP                          | Mounting Backplate attached to socket for steel guide wire  |
| LFS-12-5 B<br>LFS-24-5/8.5/10 B | I2V Halogen bulb, 5 watts<br>24V Xenon bulb, 5 watts, 8.5<br>watts or I0 watts                      |
| LFS-GLOBE                       | 2 <sup>1</sup> /2" Shatterproof Globe<br>Specify Clear, Blue, Green, Red,<br>Yellow, Pink or Purple |

12V maximum run is 300 watts; 24V maximum run is 600 watts; Sockets and cable are Black. See pages 27-28 for appropriate transformers.

\*When ordering, please specify linear feet of light socket cable, number of light sockets needed, and spacing on-center. Each order is assembled per customer specifications before it is shipped.

### **Festival Lights**

### Durable low voltage light strings give a festive look to any application.



### Diameters: 1 1/2" and 3" Polycorbonate Globes

- Clear or colored polycarbonate globes provide a secure watertight seal around bulb
- Sockets firmly attached to 12 gauge wire
- Bulb spacings: 6", 12", 18" and 24"
- Parallel wiring means loss of one bulb does not affect remaining bulbs
- 330 foot bulk reels are available or specify custom length
- Field cuttable for custom applications
- · Socket base features holes for surface mounting

| Item#        | Description   |
|--------------|---|
| FL-6         | Festival Lights, 24V  |
| FL-12        | Spacing: 6", 12", 18" and 24" available   |
| FL-18        | Bulbs and globes sold separately  |
| FL-24        |   |
| FL-BULB-5W   | 24V Festival Bulb, E-10 base, 5 watts 15,000 hours (average life)               |
| FL-I.5-COLOR | Polycarbonate Globe, diameter: 1 1/2"<br>Clear, Blue, Green, Red, Yellow, White |
| FL-3-COLOR   | Polycarbonate Globe, diameter: 3"<br>Clear, Blue, Green, Red, Yellow, White     |

<sup>\*</sup> Maximum run is 96 bulbs or 480 watts

<sup>\*</sup> See pages 27-28 for appropriate transformers.

### **Belt Light**

### The perfect solution for festive outdoor lighting!



- Great for lighting restaurant interiors, building outlines, patio lighting, gazebos, and many other applications
- Available in your choice of colors, sockets sizes and socket spacings (see below for details)
- PVC socket forms a tight weatherproof seal around the bulb
- Maximum 25 watts per socket (see page 32 for Long Life Bulbs)
- 330 foot Bulk Reels are available or specify custom length
- Field cuttable for custom applications
- 1,400 watts maximum for 330 foot reels
- For indoor and outdoor use
- 16 gauge wire

| Item#            | Description   |
|------------------|---|
| LS-C-12          | Candelabra Base Light String<br>Sockets 12" on-center, plug sold separately<br>Black, White or Green wire       |
| LS-I-15          | Intermediate Base Light String<br>Sockets 15" on-center, plug sold separately<br>Black, White or Green wire     |
| LS-M-24          | Medium Base Light String<br>Sockets 24" on-center, plug sold separately<br>Black or Green wire                  |
| LS-MS-24         | Medium Base Light String with suspended sockets, 24" on-center, plug sold separately, Black or Green wire       |
| LS-M-24-48       | 48 foot Medium Base Light String<br>Sockets 24" on-center, with plug<br>Black or Green wire                     |
| LS-MS-24-48      | 48 foot Medium Base Light String with suspended sockets, 24" on-center, with plug, Black or Green wire          |
| X-END<br>LS-PLUG | Silicone End Cap, Clear<br>Quick Plug, 2-blade, Black, for indoor use   |
| LS-I-I5-I00-WH   | Intermediate base light string with plug<br>White wire while supplies last<br>Maximum of 700 watts, 15" spacing |

Long life bulbs sold separately. See page 33.

# Chasing marquee lighting has never been so easy to create!



### Socket Height: 13/8", Diameter: 13/8"


- Use with controller for eye catching chasing effects or hardwire for "all-on" applications
- Flexible 5-wire PVC belt with 4" or 6" on-center socket spacing
- Surface mount or insert sockets through 11/4" holes
- · Field cuttable for maximum flexibility
- For indoor use only
- · Grey cable and socket

| ltem#        | Description  |
|--------------|--|
| BL-4<br>BL-6 | Custom Cut Belt Light<br>4" and 6" socket spacing, medium base<br>200 feet per roll, 15 amp maximum* |
| BL-20-60     | Belt Light, 4" socket spacing,<br>medium base*   |
| BL-40-I20    | 20 foot length has 60 sockets and 40 foot length has 120 sockets                                     |
| BL-20-40     | Belt Light, 6" Socket spacing,<br>medium base*   |
| BL-40-80     | 20 foot length has 40 sockets and 40 foot length has 80 sockets                                      |
| BLC 105      | Belt Light Controller, 5 chasing patterns, 840 watts maximum   |
| RLC-737      | Belt Light Controller<br>4 patterns plus "all-on"<br>1600 watts maximum                              |
| BL-END-CL    | End Cap  |
| BL-CLIP-CL   | Mounting Clip  |

<sup>\*&</sup>quot;All-on" run is 650 watts maximum and chasing run is 840 watts maximum per channel. Use 25 watt bulbs maximum.
Long Life Bulbs sold separately. See page 32.

### Fiber Optic Lighting

# A flexible, versatile alternative to neon and other traditional electric lighting products.



- Ideal for signs, star ceilings, building outlines, cove lighting, architectural details, fountains and swimming pools
- Multiple fiber types available for maximum versatility
- Safe no electricity in the cable itself
- Cool emits little or no heat
- Use a color wheel for color-changing effects
- Synchronize multiple metal halide units with a synchronous controller

| Fiber Optic Illuminators                    | Description  |
|---|--|
| FOI-I50-MH-C                                | Metal Halide Illuminator with color wheel and 150 watt lamp Dimensions: 12" x 11" x 6"   |
| FOI-I50MH                                   | Replacement lamp for FOI-I50-MH-C 6,000 hours (average life)                             |
| FOG-I50Q                                    | Quartz Halogen Illuminator with color wheel and 150 watt lamp Dimensions: 7" x 6.5" x 5" |
| FOB-I50Q                                    | Replacement Lamp for FOG-I50Q<br>I,500 hours (average life)                              |
| FOC-50-150Q<br>FOC-100-150Q<br>FOC-200-150Q | Fiber Connector for FOG-I50Q<br>Holds 50, 100 or 200 fibers                              |

| Side Emitting<br>Fiber Cable     | Description  |
|----------------------------------|--|
| FIB-100                          | Stranded Fiber Cable. <sup>3</sup> /8" cable with 42 strand and FIB-50. <sup>1</sup> /2" cable with 84 strand FIB-100; cluster of .75mm fibers in clear PVC jacket |
| FIBS-250<br>FIBS-375<br>FIBS-500 | Solid Fiber Cable, 1/4", 3/8" and 1/2" diameter size in clear PVC jacket   |
| DL-TRACK-4<br>MDL-TRACK-4        | "U" Shaped mounting track 4 foot sections, 3/8" and 1/2" size  |
| FO-KNIFE-L<br>FO-KNIFE-H         | Hot knife cuts stranded fiber cable<br>Light and heavy-duty capability   |








| End Emitting                              |   |
|---|---|
| Fiber Cable                               | Description   |
| FSK-300<br>FSK-300 (long)                 | Fiber Optic Star Kit, 300 fibers*<br>8-12 foot and 16-20 foot fiber lengths   |
| FOG-75C                                   | Quartz Halogen Star Illuminator<br>with twinkle wheel and 75 watt<br>lamp, Dimensions: 7" x 6.5" x 5"   |
| FOC-100-75C<br>FOC-200-75C<br>FOC-500-75C | Fiber Connector for FOG-75C<br>Holds 100, 200 or 500 fibers   |
| FSK-CWHEEL                                | Color Wheel, plastic<br>Colors: Clear, Purple, Yellow,<br>Blue, Green and Red   |
| FS.75<br>FS 1.0<br>FS 1.5<br>FS 2.0       | .75mm End Emitting Fiber 8856' per spool<br>1.0mm End Emitting Fiber 4920' per spool<br>1.5mm End Emitting Fiber 2460' per spool<br>2.0mm End Emitting Fiber 820' per spool<br>Sold as full spools only |

\* 70% of fibers are .75mm, 20% of fibers are 1.0mm, 10% of fibers are 1.5mm







LED Lighting Systems

### **LED Mini-Flex**

# Ultra bright, minimum maintenance - the ultimate high end linear light source!



### Diameter: 1/2", Bulb Spacing: 1"




- Bright! 6400°K and 4000°K
- · Minimal heat generated for maximum safety
- Long lasting bulbs up to twelve years!
   White 60,000 hours (average life)
   All other colors 100,000 hours (average life)
- Flexible
- Field cuttable for maximum flexibility
- Bulb specifications: .06 watts (White, Blue, Green);
   .03 watts (Red, Amber, Yellow)
- Voltages: 12V (White) and 120V (all colors)
- Cuttability: 12V-3"; 120V-36" (White, Green, Blue); 120V-60" (Red, Amber, Yellow)
- Maximum run distance: 240 feet–120V; 30 feet–12V
- Indoor & outdoor rated

| Item#                         | Description  |
|-------------------------------|--|
| LED-DL-COLOR<br>LED-DL-CONKIT | Bulk LED Rope Light<br>Bulk Connector Kit                              |
| DL-SPL                        | Splice Connector   |
| DL-EXT-2-KIT<br>DL-EXT-I5-KIT | Extensions – to link two sections together, 2 foot and 15 foot lengths |
| DL-CLIP/SCREW<br>DL-COND      | "U" Shaped Mounting Clip "P" Shaped Conduit Clip                       |
| DL-TRACK-4<br>DL-CHAN-MG/MS   | 4 foot Clear mounting track<br>4 foot Gold/Silver Reflective Channel   |

| Specifications |            |             |          |  |
|----------------|------------|-------------|----------|--|
|                | Watts/foot | Cuttability | Max Run  |  |
| LED-DL-WH      | .77        | 36"         | 240 feet |  |
| LED-DL-GR      | .77        | 36"         | 240 feet |  |
| LED-DL-BL      | .77        | 36"         | 240 feet |  |
| LED-DL-YE      | .47        | 60"         | 240 feet |  |
| LED-DL-RE      | .47        | 60"         | 240 feet |  |
| LED-DL-AM      | .47        | 60"         | 240 feet |  |
| LED-DL-WH-12V  | .77        | 3"          | 30 feet  |  |

# Ultra-bright, long-life flexible lighting – low maintenance and compact design.



### Dimensions: 1/4" x 5/16", Bulb Spacing: 1"

- Bright neon-like light that's easy to use!
- Flexible, ultra slim design
- Easy installation
- Long lasting bulbs up to twelve years!
   White 60,000 hours (average life)
   All other colors 100,000 hours (average life)
- Minimal heat generated for maximum safety
- Long run distances up to 150 feet
- · Field cuttable for maximum flexibility
- Voltage: 12V (all colors)
- Bulb Specifications: .06 watt (White, Blue, Green)
   .03 watt (Yellow, Red, Amber)
- Floor and aisle lighting retrofit

| Item#             | Description  |
|-------------------|--|
|                   | Bulk LED Rope Light<br>Bulk Connector Kit  |
| LED-MDL-SPL       | Splice Connector   |
| LED-MDL-EXT-2-KIT | Two foot extension to link two sections together   |
| PU<br>PT/PC       | Clear polycarbonate "U" channel<br>PVC Channel with a removable<br>cap for use with concrete |

| Specifications |                               |    |         |  |
|----------------|-------------------------------|----|---------|--|
|                | Watts/foot Cuttability Max Ru |    |         |  |
| LED-MDL-WH     | .77                           | 3" | 30 feet |  |
| LED-MDL-GR     | .77                           | 3" | 30 feet |  |
| LED-MDL-BL     | .77                           | 3" | 30 feet |  |
| LED-MDL-YE     | .47                           | 3" | 30 feet |  |
| LED-MDL-RE     | .47                           | 3" | 30 feet |  |
| LED-MDL-AM     | .47                           | 3" | 30 feet |  |

### **LED Clip Light Bulbs**

# A bright, long lasting, miniature bulb great for year-round lighting. Safe, low voltage.



### Bulb Height: 5/8", Diameter: 5/16"

- Bright and safe low voltage LED bulbs eliminate shock hazards
- Long lasting bulbs up to twelve years!
   White 60,000 hours (average life)
   All other colors 100,000 hours (average life)
- Energy efficient only uses .2 watt per bulb
- Colors: Amber, Blue, Green, Red, Yellow and White

# Item # Description CLED-AM-I2/24 LED Bulbs, I2V CLED-BL-I2/24 Amber, Blue, Green, Red, Yellow and White CLED-RE-I2/24 CLED-YE-I2/24 CLED-WH-I2/24

|        | 12V LED Specifications |                |                  |            |                         |
|--------|------------------------|----------------|------------------|------------|-------------------------|
| Color  | Watts                  | Maximum<br>Run | Viewing<br>Angle | Wavelength | Average Life (in hours) |
| Amber  | .2                     | 365 bulbs      | 30°              | 605mm      | 100,000                 |
| Blue   | .2                     | 365 bulbs      | 30°              | 468mm      | 100,000                 |
| Green  | .2                     | 365 bulbs      | 30°              | 520mm      | 100,000                 |
| Red    | .2                     | 365 bulbs      | 30°              | 630mm      | 100,000                 |
| Yellow | .2                     | 365 bulbs      | 30°              | 585mm      | 100,000                 |
| White  | .2                     | 365 bulbs      | 30°              | n/a*       | 60,000                  |


 $<sup>\</sup>ensuremath{^*}$  The color White is made by using blue LEDs covered with a phosphor gas lens.

|        | 24V LED Specifications |                |                  |            |                            |
|--------|------------------------|----------------|------------------|------------|----------------------------|
| Color  | Watts                  | Maximum<br>Run | Viewing<br>Angle | Wavelength | Average Life<br>(in hours) |
| Amber  | .2                     | 730 bulbs      | 30°              | 605mm      | 100,000                    |
| Blue   | .2                     | 730 bulbs      | 30°              | 468mm      | 100,000                    |
| Green  | .2                     | 730 bulbs      | 30°              | 520mm      | 100,000                    |
| Red    | .2                     | 730 bulbs      | 30°              | 630mm      | 100,000                    |
| Yellow | .2                     | 730 bulbs      | 30°              | 585mm      | 100,000                    |
| White  | .2                     | 730 bulbs      | 30°              | n/a*       | 60,000                     |

 $<sup>\</sup>ensuremath{^*}$  The color White is made by using blue LEDs covered with a phosphor gas lens.

### **LED Festoon Bulbs**

# LED Festoon bulbs are perfect for indirect lighting where color is needed.



- Bright and safe low voltage LED bulbs add color to any application
- Long lasting bulbs up to twelve years!
   White 60,000 hours (average life)
   All other colors 100,000 hours (average life)

| Item #     | Description                                  |
|------------|--|
| LEDF-BL-12 | Colored LED Festoon bulbs, .25 watt per bulb |
| LEDF-GR-I2 | 100,000 hours (average life)                 |
| LEDF-RE-I2 | Yellow, Red, Green, Blue and White           |
| LEDF-WH-I2 |  |
| LEDF-YE-I2 |  |

### LED MR16's

# Spectacular LED effects in a familiar shape that fit most low voltage MR 16 fixtures!



Diameter: 1 1/16", Bulb Height: 15/8"


- Multiple lighting LED effects color cross fades, color washes and sparkles
- Long lasting bulbs up to twelve years!
   White 60,000 hours (average life)
   RGB and all other colors 100,000 hours (average life)
- 12V DC—not compatible with AC transformers

| Item#       | Description  |
|-------------|--|
| LED-MR-16   | Color changing LED's – stand<br>alone mode or use Controller<br>for multiple LED effects |
| LEDMR 16-WH | Color Spot LED MR 16, 2.4 watts,   |
| LEDMR 16-BL | White, Blue, Green, Red, Yellow  |
| LEDMR 16-GR | and Orange   |
| LEDMR 16-RE |  |
| LEDMR 16-YE |  |
| LEDMR 16-OR |  |

Color-changing LED MR16's contain 17 RGB LED's per bulb. Single-color LED MR16's contain 18 monochromatic LED's per bulb.

### **LED Tube Light**


# Energy efficient single color or color changing lighting specifically designed for architectural elements.




### 3/4" polycarbonate tube

- Linkable tubes can be installed end-to-end
- Cool operating LED's produce virtually no heat
- Long lasting bulbs up to twelve years!
   White 60,000 hours (average life)
   RGB and all other colors 100,000 hours (average life)
- RGB LED Tubes project thousands of colors with RGB controller
- Color Temperature White: 2800°K and 5000°K


| Item#            | Description                              |
|------------------|--|
| LEDT-COLOR-24/FT | Single Color LED Tube, I2V DC            |
| LEDT-COLOR-48/FT | 24 or 48 LED's per foot                  |
|                  | Red, Amber, Green, White, Blue           |
|                  | Sold in 6" increments                    |
| LEDT-RGB-24/FT   | RGB LED Tube, I2V DC                     |
| LEDT-RGB-48/FT   | 24 or 48 LED's per foot                  |
|                  | Sold in 9" increments                    |
| LEDMC-8.5        | RGB Master Controller,                   |
|                  | Functions: Color fade, select            |
|                  | color and brightness                     |
| LEDSL-12         | RGB Slave Controller to be linked to     |
|                  | LEDMC-8.5 on runs of 16 foot or more     |
| LEDCC            | Cable for linking master & slave         |
| LEDCC-CON        | Male and female connectors               |
| LEDT-CLIP        | Mounting Clip, I" long                   |
| LEDPS-3.3        | I2V DC power supply                      |
| LEDPS-5.0        | 3.5, 5.0, 8.5 amps                       |
| LEDPS-8.5        | Dimensions: 8" x 4" x 1.5",              |
| LEDPS-I2.5       | 12.5 amps, dimensions: 8" x 5" x 2"      |
| LEDPS-18         | and 18 amps, dimensions: 8" x 4" x 3"    |
| LED-DR-I2        | Regulated Driver, up to 25 watts, I2V DC |







RGB Tubes create intense and dramatic lighting effects allowing the ultimate in color control.



| Viewing Angles Available |                                     |                                     |  |  |
|--------------------------|-------------------------------------|-------------------------------------|--|--|
| 30° 50° 80°              |                                     |                                     |  |  |
| Characteristics          | Strong intensity<br>High visibility | Medium intensity<br>Good visibility | Diffused<br>Softened effect              |  |
| Applications             | Signs<br>Outlines                   | Backlighting                        | Coves<br>Color washes<br>Accent lighting |  |

| Specifications              |            |           |                 |                           |                        |  |
|-----------------------------|------------|-----------|-----------------|---------------------------|------------------------|--|
|                             | Watts/foot | Amps/foot | Max Tube<br>Run | Max Run per<br>Controller | Add'l Run<br>per Slave |  |
| LED 24/FT<br>(single color) | 2.4        | .25       | I2 feet         | n/a                       | n/a                    |  |
| LED 48/FT<br>(single color) | 4.8        | .50       | 8 feet          | n/a                       | n/a                    |  |
| LED 24/FT<br>(RGB)          | 2.4        | .24       | 12 feet         | 16 feet                   | 21 feet                |  |
| LED 48/FT<br>(RGB)          | 4.8        | .50       | 9 feet          | 8 feet                    | 10 feet                |  |



### **LED Mini Light Strings**

### Save 80-90% in electricity costs with cool burning Mini Lights in a size C6.



- Uses 80 90% less electricity
- Long lasting bulbs up to twelve years! White 60,000 hours (average life) All other colors 100,000 hours (average life)
- Rugged no glass bulbs to break
- Minimal heat generated for maximum safety
- Brillant colors that will not fade or flake
- Wired in parallel when one bulb fails the rest stay lit
- 4" bulb spacing on 20 gauge wire
- For indoor and outdoor use
- Individual bulbs can be changed easily
- Plug strings end-to-end

C6LED35-G-COLOR LED C6 Light String, 120V, 1.4 watts 35 lights per string, Green wire Multi, White, Red, Green, Blue and Yellow

### **LED Edgelit Signage**

Sleek, low maintenance bases light up corporate ID's, product recognition and are an energy efficient EXIT sign alternative.



Lengths: 12", 18" and 24". Acrylic will be 3/8" shorter than the length of the base

- Eye catching neon-like glow
- Bright colors that will not fade
- Custom designs, acrylic sold separately
- Cool operating emits virtually no heat
- Long lasting bulbs up to twelve years! White 60,000 hours (average life) All other colors 100,000 hours (average life)
- · Wall mount, ceiling mount and desk/counter bases available
- · Acrylic panel available in "ice-break" and solid edge
- Acrylic will be 3/8" shorter than the length of the base

| Item#    | Description                     |
|----------|---------------------------------|
| ELBLED-* | LED Edgelit Base                |
|          | Red, Amber, Blue, Green, Orange |
|          | and White                       |
|          | <sup>3</sup> /8" thick acrylic  |

<sup>\*</sup>Specify mounting, color and acrylic edge style



### Bright, energy efficient LED's bring light to dark areas of the home.









NL-01 (White)

- Diameter: 2 3/8", Height: 11/8"
- No heat
- · Very low energy usage
- No bulb to replace
- · Low profile design
- Long life bulb lasts up to ten years!
   White LEDs 60,000 hours (average life)
   Blue and RGB 100,000 hours (average life)

### NL-02 (Blue)

• Diameter: 2 3/8", Height: 11/8"

### NL-03 (RGB-Color Changing)

• Diameter: 2 3/8", Height: 11/8"





### NL-04

- High/Low LED Night Lite
- Motion sensor and photocell
- · "Low" level comes on at dusk
- When "motion" is detected, light turns to "High" light level





### NL-05

- Multi function LED Night Lite
- Motion sensor and photocell
- Options include: "motion", "always-on" and "photocell" mode





### NL-06

- Three-in-One Utility LED Night Lite
- Rechargeable flash light
- Photocell
- Emergency light in the event of power failure





### NL-07

- Fiber Optic LED Night Lite
- Photocell
- Changeable Fiber Optic cartridge (Blue, Green and White included)



### **Magnetic Transformers**

# Efficient, inexpensive and compact for your low voltage lighting needs.



- · Whisper quiet operation, even when dimmed
- Compact size and innovative design has reduced overall dimensions
- Efficient and dependable 94% efficiency rating
- Easy installation, multiple knockouts available
- · Magnetic circuit breakers protect each circuit
- Five year warranty
- Rating: NEMA 3R for indoor and outdoor use
- Boost tap for longer runs
- Black powder coated finished with stainless steel enclosure

| Item#                    | Description   |
|--------------------------|---|
| TR-I50-I2<br>TR-I50-24   | I50 watts, I2V, (1) I5 amp circuit<br>I50 watts, 24V, (1) 7 amp circuit<br>Dimensions: 8.5"x3.5"x3.5"       |
| TR-300-I2<br>TR-300-24   | 300 watts, I2V, (1) 25 amp circuit<br>300 watts, 24V, (1) I5 amp circuit<br>Dimensions: 9"x4.5"x4.5"        |
| TR-300-PT-I2             | 300 watts, I2V with photocell and timer<br>Dimensions: I0"x4.5"x4.5"  |
| TR-600-I2<br>TR-600-24   | 600 watts, 12V, (2) 25 amp circuits<br>600 watts, 24V, (1) 15 amp circuit<br>Dimensions: 9.5"x5"x5"         |
| TR-900-I2<br>TR-900-24   | 900 watts, 12V, (3) 25 amp circuits<br>900 watts, 24V, (2) 25 amp circuits<br>Dimensions: 10.5"x5.5"x5.5"   |
| TR-I200-I2<br>TR-I200-24 | I200 watts, I2V, (4) 25 amp circuits<br>I200 watts, 24V, (2) 25 amp circuits<br>Dimensions: I0.5"x6.5"x6.5" |

### **Electronic Transformers**

# Compact electronic transformers pack a powerful punch.



- · Overload and short circuit protection
- Multiple knockouts on 150 watt and 300 watt models
- DC regulated transformers allow for longer runs without voltage drop

| Item#                          | Description  |
|--------------------------------|--|
| TRE-75-12<br>TRE-75-24         | 75 watts, hardwire, I2V and 24V<br>Remote transformer in steel housing<br>Overload and short circuit protection  |
| TRE-80-12                      | 80 watts, hardwire, I2V<br>Remote transformer in steel housing<br>Overload and short circuit protection  |
| TRE-I50-I2<br>TRE-I50-24       | I50 watts, hardwire, I2V and 24V Remote transformer in steel housing Overload and short circuit protection Features 6 knockouts for easy installation                                    |
| TRE-300-12<br>TRE-300-24       | 300 watts, hardwire, I2V and 24V<br>Remote transformer in steel housing<br>Overload and short circuit protection<br>Features 6 knockouts for easy<br>installation                        |
| TRE-I50-I2-DC<br>TRE-300-I2-DC | I50 or 300 watts, hardwire, I2V DC<br>Remote transformer in steel housing<br>Allows for longer maximum run<br>distances (up to 25 feet)<br>Features 6 knockouts for easy<br>installation |

See page 28 for other electronic transformer models.

### **Electronic Transformers**

### **Plug-in Electronic Transformers**



### ALTR60B\*/ALTR60BP\*

- 60 watt hardwire 12V remote transformer in plastic housing
- Auto reset/thermal protection against heat and shorts
- \* B=Bulk and BP=Blister Pack



### ALTR80B\*/ALTR80BP\*

- · 80 watt hardwire 12V remote transformer in plastic housing
- Auto reset/thermal protection against heat and shorts
- \* B=Bulk and BP=Blister Pack



### ALTR105B\*/ALTR105BP\*

- 105 watt hardwire 12V remote transformer in plastic housing
- · Auto reset/thermal protection against heat and shorts
- \* B=Bulk and BP=Blister Pack



### ALTR150B\*/ALTR150BP\*

- 150 watt hardwire 12V remote transformer in plastic housing
- · Auto reset/thermal protection against heat and shorts
- \* B=Bulk and BP=Blister Pack



- 60 watt plug-in 12V transformer
- Two foot lead with puck connector block
- On/off roll switch
- Auto reset/thermal protection
- · Blister Pack



- 60 watt remote 12V transformer
- · 8 foot power cord with 2 foot lead and puck connector block
- On/off roll switch
- Auto reset/thermal protection
- Blister Pack



- 120 watt remote 12V transformer
- · 8 foot power cord with 2 foot lead and puck connector block
- On/off roll switch
- Auto reset/thermal protection
- Blister Pack

### **Dimmers**



### ALDIM200

- · 200 watt replacement lamp dimmer, 120V
- Includes gold knob
- For use with torchieres and table lamps



- 500 watt replacement lamp dimmer, 120V
- Includes gold knob
- For use with torchieres and table lamps



### ALTDIM

- 200 watt Halogen, Xenon and Incandescent dimmer, 120V
- · Three light levels, plus off
- · Converts any lamp with metal to touch control
- Easy to install, universal replacement





- 150 watt Halogen, Xenon and Incandescent dimmer, 120V
- Converts any lamp with metal to touch lamp
- · Three light levels





### ALDIMF500/ALDIMF500W

- 500 watt plug-in foot dimmer
- Sturdy design, fused
- · Slide control allows easy dimming

### **Touch Control Dimmers**





### **ALTDPI**

- 200 watt Halogen, Xenon and Incandescent dimmer, 120V
- Converts any lamp with metal to a touch lamp
- Use regular bulb instead of 3-way bulb
- · No wiring, just plug-in light fixture



### **ALTPDPI**

- 200 watt Halogen, Xenon and Incandescent dimmer, 120V
- · Converts lamp to touch control
- No wiring, just plug-in light fixture
- 3-Level touch pad dimming for tabletops and workstations



### ALLVPTDIM



- · 300 watt Halogen, Xenon and Incandescent dimmer
- Converts 120V products to touch control
- No wiring, just plug-in
- · Hinge or touch pad dimmer
- Touch pad allows for 3-Level control (Hi/Medium/Low) and off



### ALTPDIM



- Hinge or Touch Pad Dimmer
- 300 watt Halogen, Xenon and Incandescent, 120V
- Touch pad allows for 3-Level control (Hi/Medium/Low) and off
- Attach up to five 60 watt plug-in puck light transformers

### **Lighting Controls - Photocells**

# ALSENSI

- Automatic Light Control
- Use dial to adjust light sensitivity
- Automatic "on" at dusk and "off" at dawn
- 150 watts maximum, Incandescent lamps only



### ALSENSPAR

- Automatic Outdoor Light Control
- 150 watts maximum, Incandescent lamps only
- Short stem design fits inside most exterior fixtures
- Twist shutter housing to adjust light sensitivity



### ALSENPI

- Automatic Light Control—Plug-in
- 300 watts maximum
- · Automatic "on" at dusk and "off" at dawn
- Incandescent lamps only
- · For indoor use only



## ALSENSPIDIM CULJUS




- Digital "Auto Light Control" for Compact Fluorescent (PL) bulbs
- Automatic "on" at dusk and "off" at dawn
- 300 watts maximum

### **Controllers**

### Heavy-duty chase controllers provide years of trouble free service.







- Fuse protection
- AC operation
- Limited lifetime warranty


| Item#    | Hardwire Description                    |
|----------|---|
| CON-3-2  | Controller, 3 amps per channel          |
| CON-3-3  | One direction chase with speed control  |
| CON-3-4  | 2, 3 or 4 channels, I2V/24V/I20V, fused |
| CON-6-2  | Controller, 6 amps per channel          |
| CON-6-3  | One direction chase with speed control  |
| CON-6-4  | 2, 3 or 4 channels, I2V/24V/I20V, fused |
| CON-10-2 | Controller, 10 amps per channel         |
| CON-10-3 | One direction chase with speed control  |
| CON-10-4 | 2, 3 or 4 channels, I2V/24V/I20V, fused |

Custom controllers available. Please call for assistance.

### **Decorative Plant Light**

### Create dramatic accent lighting for indoor plants.







- Adjustable, compact and ready-to-use
- Stakes anchor lights firmly into soil
- · Each pair of lights is pre-wired onto six-foot cord with convenient On/Off switch
- Clear, protective lamp cover

| Item#     | Description   |
|-----------|---|
| DPL-90000 | Decorative Plant Light - Retail Box<br>Includes (2) 10 watt Halogen<br>light stakes and two spare<br>bulbs for future use |

Plant Lights are for indoor use only.



### **Decorative Up Light**

Adjustable mini spot that highlights artwork, architectural details, foliage and collectibles.



Height: 6", Length: 6 3/16", Width: 4 7/8"



- Sleek and compact only 6" high
- Ready to use just plug it in
- Full 360° swivel
- · Convenient On/Off switch

| Item#   | Description                      |
|---------|----------------------------------|
| ALUL50S | Decorative Up Light - Retail Box |
| ALUL50W | Includes (1) 50 watt lamp        |
|         | Silver and White                 |

Decorative Up Lights are for indoor use only.



### High quality bulbs that last—available in a wide variety of shapes and colors!







**BAI5-Frosted** 



B11\$14-Yellow



B7.5\$11-Blue



B10S11-Green



- Extra thick glass
- Long life filaments
- · Waterproof colors
- · Nickel base
- Extra filament supports
- 3,000-8,000 hours (average life)

| ltem#   | Description   |  |  |  |  |
|---|---|--|--|--|--|
| B7.5S II-CL<br>B7.5S II-COLOR                   | Medium base B7.5SII bulb<br>7.5 watts, 8,000 hours, 130V, G12.5<br>Clear, Frosted, Red, Blue,<br>Green, Yellow, Amber, White          |  |  |  |  |
| BIISI4-CL<br>BIISI4-COLOR                       | Medium base B II S I4 bulb<br>II watts, 8,000 hours, I30V,<br>Clear, Frosted, Red, Blue,<br>Green, Yellow, Amber, White               |  |  |  |  |
| B IOS II-CL<br>B IOS II-COLOR                   | Intermediate base B IOS II bulb<br>IO watts, 8,000 hours, I30V<br>Clear, Frosted, Red, Blue,<br>Green, Yellow, Amber, White           |  |  |  |  |
| B7.5C-CL<br>B7.5C-COLOR                         | Candelabra base B7.5C bulb<br>7.5 watts, 8,000 hours, 130V, G II<br>Clear, Frosted, Red, Blue,<br>Green, Yellow, Amber, White         |  |  |  |  |
| C7-5-COLOR                                      | Candelabra Base C7 bulb<br>5 watts, 3,000 hours, 130V<br>Clear, Red, Blue, Green, Pink<br>Purple, Yellow, Teal, Amber, Assorted       |  |  |  |  |
| C9-7-COLOR                                      | Intermediate Base C9 bulb<br>7 watts, 3,000 hours, 130V<br>Clear, Red, Blue, Green,<br>Pink, Purple, Yellow, Teal,<br>Amber, Assorted |  |  |  |  |
| BA 19-CL  | Medium base, A I9 bulb, 25 watts, 3,000 hours, I30V clear   |  |  |  |  |
| BA 15-FR  | Medium base, A I5 bulb, I5 watts, 3,000 hours, I30V clear   |  |  |  |  |
| Bulbs are sold in full box (25) multiples only. |   |  |  |  |  |

### Dramatic lighting accents that simply clip on to an MR 16 lamp!



MR-HON





MR-DB-RED



MR-DB-GREEN





MR-CLIP-FIL-BLUE



MR-CLIP-FIL-GREEN



MR-CLIP-FIL-RED





- Easy to use
- Decorative and unique
- Durable made of stainless steel
- Use together in creative combinations!

| Item#                | Description   |
|----------------------|---|
| MR-BD-BK<br>MR-BD-SI | Barndoors, Black and Silver<br>Direct light, reduce glare<br>Can be used in pairs   |
| MR-LOU-P             | Parallel Louvers, Black<br>Rotate for glare protection,<br>combine with barndoors   |
| MR-HON               | Honey Comb Filter, Black<br>Reduce glare and peripheral light,<br>combine with barndoors<br>Requires MR-CLIP, sold separately |
| MR-DB                | Decorative Clip Holder for MR-DB-COLOR, sold separately   |
| MR-DB-COLOR          | Decorative Color Ball<br>Three eye catching colors: Red,<br>Green and Blue<br>Requires MR-DB, sold separately                 |
| MR-CLIP              | Filter Clip, Black<br>Use with MR-HON or<br>MR-FIL, sold separately   |
| MR-FIL-COLOR         | Colored Filter Create eye catching color washes in Red, Green and Blue Requires MR-CLIP, sold separately                      |

### **Bulb Specifications**

|           |                       | Item Number | Volts | Watts | Lumens | Approx. Color<br>Temp (Kelvin) | Average Life (in hours)    | Base      |
|-----------|-----------------------|-------------|-------|-------|--------|--------------------------------|----------------------------|-----------|
|           |                       | AL20B       | I2V   | 20w   | 145    | 2700                           | 2,000                      | G4        |
|           | (CX (-1-0)            | ALX IOBX    | I2V   | 10w   | 140    | 2700                           | 10,000                     | G4        |
|           |                       | ALPXP20BP   | I2V   | 20w   | 235    | 3000                           | 10,000                     | G4        |
|           |                       | BC-3-I2     | I2V   | 3w    | 14     | 2550                           | 3,000                      | Wedge     |
|           |                       | BX-5-12     | I2V   | 5w    | 33     | 2550                           | 10,000                     | Wedge     |
| 12 Volts  |                       | CL-BULB-I2  | I2V   | .5w   | 2      | 2500                           | 25,000                     | Wedge     |
| >         |                       | FSL-5-12    | I2V   | 5w    | 33     | 2550                           | 20,000                     | Festoon   |
| 12        | <b>d</b>              | FSL-10-12   | I2V   | 10w   | 83     | 2650                           | 20,000                     | Festoon   |
|           |                       | FSL-5F-I2   | I2V   | 5w    | 33     | 2550                           | 15,000                     | Festoon   |
|           | n                     | FSL-10F-12  | I2V   | 10w   | 83     | 2700                           | 15,000                     | Festoon   |
|           | -                     | MR-II-I2-20 | I2V   | 20w   | 220    | 3000                           | 2,000                      | G4        |
|           |                       | ltem Number | Volts | Watts | Lumens | Approx. Color<br>Temp (Kelvin) | Average Life (in hours)    | Base      |
|           |                       | BC-3-24     | 24V   | 3w    | 14     | 2650                           | 3,000                      | Wedge     |
|           |                       | BX-5-24     | 24V   | 5w    | 33     | 2650                           | 10,000                     | Wedge     |
|           | <b>\begin{align*}</b> | CL-BULB-24  | 24V   | .96w  | 4      | 2500                           | 25,000                     | Wedge     |
|           |                       | FSL-5-24    | 24V   | 5w    | 33     | 2550                           | 20,000                     | Festoon   |
| Ŋ         | 9                     | FSL-10-24   | 24V   | 10w   | 83     | 2650                           | 20,000                     | Festoon   |
| olt       |                       | FSL-5F-24   | 24V   | 5w    | 31     | 2550                           | 15,000                     | Festoon   |
| 24 Volts  | <b>u</b> b            | FSL-10F-24  | 24V   | 10w   | 79     | 2650                           | 15,000                     | Festoon   |
| 2         | -                     | MR-II-24-20 | 24V   | 20w   | 230    | 2700                           | 2,200                      | G4        |
|           |                       | TL-BULB-24  | 24V   | .96w  | 4      | 2500                           | 25,000                     | Wedge     |
|           |                       | Item Number | Volts | Watts | Lumens | Approx. Color<br>Temp (Kelvin) | Average Life<br>(in hours) | Base      |
|           |                       | ALFL8B      | 120V  | 8w    | 440    | 3100                           | 8,000                      | T4 Bi-Pin |
|           | -                     | ALFL 16B    | 120V  | 16w   | 960    | 3100                           | 8,000                      | T4 Bi-Pin |
| olts      | 32                    | ALLVP20B    | 120V  | 20w   | 145    | 2600                           | 2,500                      | G8        |
| 120 Volts |                       | LHC35B-BP   | 120V  | 35w   | 390    | 2600                           | 2,500                      | G8        |
|           |                       | LXCP-20BP   | 120V  | 20w   | 165    | 2600                           | 8,000                      | G8        |

### **Photometric Data**

| Ultra Thin Fluorescent Light |          |  |  |  |  |
|------------------------------|----------|--|--|--|--|
| A) 28.8                      | A1) 33.2 |  |  |  |  |
| B) 32.9                      | B1) 35.9 |  |  |  |  |
| C) 29.2                      | C1) 30.5 |  |  |  |  |
| D) 23.8                      | D1) 23.2 |  |  |  |  |

| Clear Rope Light |         |  |
|------------------|---------|--|
| A) 5.2           | A1) 4.6 |  |
| B) 5.6           | B1) 5.3 |  |
| C) 5.4           | C1) 5.3 |  |
| D) 4.9           | D1) 4.7 |  |

| Brite-Line |         |  |
|------------|---------|--|
| A) 9.4     | A1) 8.3 |  |
| B) 10.2    | B1) 9.9 |  |
| C) 9.3     | C1) 9.3 |  |
| D) 8.6     | D1) 7.8 |  |

| Fluorescent Task Light |          |  |
|------------------------|----------|--|
| A) 15.8                | A1) 17.5 |  |
| в) 17.6                | B1) 19.2 |  |
| C) 13.5                | C1) 15.2 |  |
| D) 9.5                 | D1) 10.3 |  |

| -12' | A - 12' | A1 |  |
|------|---------|----|--|
|      |         |    |  |

Data shown above, expressed in foot candles, is a result of a single fixture, with the exception of Clear Rope Light. Counter top reflectance 15%. Rear wall reflectance 50%. See diagram for points

of measurement.

| Halogen 120V Puck Light |          |  |
|-------------------------|----------|--|
| A) 21.1                 | A1) 11.3 |  |
| B) 27.1                 | B1) 12.7 |  |
| C) 18.1                 | C1) 10.1 |  |
| D) 10.2                 | D1) 8.0  |  |
| <del></del>             |          |  |

| 21" Adjustable Fluorescent Light |           |  |  |
|----------------------------------|-----------|--|--|
| A) 100.7                         | A1) 101.0 |  |  |
| В) 99.6                          | B1) 105.7 |  |  |
| C) 66.9                          | C1) 71.0  |  |  |
| D) 39.0                          | D1)41.1   |  |  |

| Halogen 12V Puck Light |          |  |
|------------------------|----------|--|
| A) 30.8                | A1) 21.6 |  |
| в) 37.7                | B1) 26.0 |  |
| C) 27.8                | C1) 20.8 |  |
| D) 14.7                | D1) 12.9 |  |

| 16" Halogen Under Cabinet Light |          |  |  |
|---------------------------------|----------|--|--|
| A) 53.8                         | A1) 53.5 |  |  |
| в) 63.9                         | B1) 62.4 |  |  |
| C) 51.8                         | C1) 51.7 |  |  |
| D) 33.9                         | D1) 35.0 |  |  |

| Xenon 120V Puck Light |          |  |
|-----------------------|----------|--|
| A) 23.2               | A1) 12.5 |  |
| B) 31.3               | B1) 14.7 |  |
| C) 19.1               | C1) 12.9 |  |
| D) 10.1               | D1) 9.8  |  |

| 16" Xenon Under Cabinet Light |          |  |  |
|-------------------------------|----------|--|--|
| A) 43.5                       | A1)41.1  |  |  |
| B) 49.3                       | B1) 47.0 |  |  |
| C) 39.9                       | C1) 38.1 |  |  |
| D) 26.5                       | D1) 26.0 |  |  |

| Xenon 12V Puck Light |          |  |
|----------------------|----------|--|
| A) 33.9              | A1) 23.9 |  |
| B) 43.6              | B1) 30.1 |  |
| C) 29.3              | C1) 26.5 |  |
| D) 14.6              | D1) 15.8 |  |

### **Universal Accessories**

| Direct Wire Boxes | Item Number               | Description   | Compatibility   |
|-------------------|---------------------------|---|---|
|                   | ALHWBOX<br>ALHWBOX-WH     | Direct Wire Box with (2) 120V outlets (2) On/Off switches, Black or White               | Use with I20V Xenon and Halogen Plug-in<br>Under Cabinet Lights, I20V Xenon and<br>Halogen Puck Lights and all Fluorescent Task<br>Light Fixtures |
|                   | ALSLHWBOX<br>ALSLHWBOX-WH | Slim Line Direct Wire Box with (2)<br>molex outlets rated at 15 amps,<br>Black or White | Use with I20V Xenon and Halogen Plug-in<br>Under Cabinet Lights, I20V Xenon and<br>Halogen Puck Lights and all Fluorescent Task<br>Light Fixtures |

| Linkable Connectors: | Item Number  | Description   | Compatibility   |
|----------------------|--|---|---|
|                      | ALLVPEX I2<br>ALLVPEX I2WH<br>ALLVPEX24<br>ALLVPEX24WH | I2" and 24" Extension cables link up<br>to six fluorescent task lights and up<br>to ten incandescent light fixtures<br>Black or White | I20V Xenon and Halogen Puck Lights and all<br>Fluorescent Task Light Fixtures |

| Power Cords: | Item Number                          | Description  | Compatibility   |
|--------------|--------------------------------------|--|---|
|              | ALLVPPC6<br>ALLVPPC6WH<br>ALLVPPC6-B | 6 foot Power cords link up to six<br>fluorescent task lights and up to ten<br>incandescent light fixtures<br>Black (Bulk or Blister Pack) and<br>White (Blister Pack only) | I20V Xenon and Halogen Puck Lights and all<br>Fluorescent Task Light Fixtures |

| Dimmer: | Item Number | Description  | Compatibility                      |
|---------|-------------|--|------------------------------------|
|         | ALLVPTDIM   | Touch Pad Dimmer for I20V products 300 watt touch dimmer with 6" input cord and 6" output cord | I20V Xenon and Halogen Puck Lights |

| Power Strip: | Item Number | Description   | Compatibility                                |
|--------------|-------------|---|--|
|              | PS-6        | I5 amps maximum<br>Six outlets available<br>Fused for safety<br>Six foot power cord<br>Bulk packaging | Use with any 120V plug-in electrical product |



### AMERICAN LIGHTING

BRIGHT IDEAS . INNOVATIVE PRODUCTS

### **Corporate Headquarters**

American Lighting, Inc.
7660 East Jewell Avenue, Suite A
Denver, Colorado 80231
800-880-1180 • Order Fax 303-695-7633
www.americanlighting.com

### **Showrooms**

Dallas Market Center #4408, Dallas, TX Corporate Offices, Denver, CO