




Outdoor Lighting Quick Reference Guide

Lithonia Lighting has been the Best Value in Lighting™ for over 75 years, providing the industry’s broadest line of commercial, industrial, and residential lighting. We bring quality, reliability, and solid performance to our customers, making Lithonia Lighting the #1 selling brand in North America across multiple lighting product categories.

Area Lighting

	D-Series Area Luminaires			RADEAN Series	
	 DSX0 LED	 DSX1 LED	 DSX2 LED	 RAD1 LED	 RADPT LED
Value Proposition in 30 Seconds	The all-new D-Series features a refined, contemporary design that seamlessly blends into any environment. DSX offers leading-edge optical performance with 15 distribution patterns for superior uniformity, wider pole spacings, and unmatched corner and backlight control.			Architecturally stunning by day, visually comfortable illumination by night, the Radean family is ideal for pedestrian spaces.	
PERFORMANCE					
Lumen Packages*	5,000 - 21,000 lumens 34W - 170W	7,000 - 35,000 lumens 51W - 279W	20,000 - 60,000 lumens 135W - 466W	P1 - 3,000 lumens, 25W P2 - 5,000 lumens, 38W P3 - 7,000 lumens, 54W P4 - 11,000 lumens, 86W P5 - 16,000 lumens, 122W	P1 - 3,000 lumens, 25W P2 - 5,000 lumens, 38W P3 - 7,000 lumens, 54W P4 - 11,000 lumens, 86W P5 - 15,000 lumens, 122W
Voltage	MVOLT (120 - 277V) HVOLT (347 - 480V) XVOLT (277 - 480V)			MVOLT (120 - 277V) HVOLT (347 - 480V)	
CORRELATED COLOR TEMPERATURE/COLOR RENDERING INDEX					
CCTs	3000K / 70 or 80 CRI 4000K / 70 or 80 CRI 5000K / 70 or 80 CRI			3000K / 80 CRI 4000K / 80 CRI	
CRI				5000K / 80 CRI	
OPTIONAL CONTROLS & PATH OF EGRESS					
Motion Sensor	High/Low Motion Sensor with Integral Photocell			High/Low Motion Sensor (see SBOR accessory)	
nLight® AIR	Yes			Yes (integral; see rSBOR accessory)	
Emergency Back Up	-			-	
SERVICE PROGRAMS					
Design Select or Contractor Select				N/A	N/A


*Nominal lumens shown. Varies by optic and CCT. Consult specification sheets for more detailed information.

	RSX LED Area Luminaires				ESX LED Area Luminaire
	 RSX1 LED	 RSX2 LED	 RSX3 LED	 RSX4 LED	 ESX1 LED
Value Proposition in 30 Seconds	The RSX LED area luminaires are a complete solution for both renovation and new construction applications where value, an extensive range of options and industry-leading delivery are required.				The ESX LED area luminaire provides the best value in area lighting with three configurations in stock at all Acuity distribution centers.
PERFORMANCE					
Lumen Packages*	P1 - 7,000 lumens, 51W P2 - 10,000 lumens, 72W P3 - 14,000 lumens, 109W P4 - 14,000 lumens, 109W	P1 - 11,000 lumens, 71W P2 - 17,000 lumens, 111W P3 - 22,000 lumens, 147W P4 - 25,000 lumens, 187W P5 - 29,000 lumens, 210W P6 - 31,000 lumens, 244W	P1 - 27,000 lumens, 194W P2 - 30,000 lumens, 222W P3 - 35,000 lumens, 266W P4 - 40,000 lumens, 312W	P1 - 40,000 lumens, 275W P2 - 45,000 lumens, 320W P3 - 50,000 lumens, 369W P4 - 55,000 lumens, 431W P5 - 62,000 lumens, 483W P6 - 69,000 lumens, 546W	P2 - 14,000 lumens / 8,000 lumens, 98W / 50W P2 - 25,000 lumens / 21,000 lumens, 190W / 146W
Voltage	MVOLT (120 - 277V) HVOLT (347 - 480V) XVOLT (277 - 480V)				MVOLT (120 - 277V)
CORRELATED COLOR TEMPERATURE/COLOR RENDERING INDEX					
CCTs	3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI				4000K / 70 CRI 5000K / 70 CRI
CRI					
OPTIONAL CONTROLS & PATH OF EGRESS					
Motion Sensor	High/Low Motion Sensor with Integral Photocell (using nLight AIR)				-
nLight® AIR	Yes				-
Emergency Back Up	-				-
SERVICE PROGRAMS					
Design Select or Contractor Select					

*Nominal lumens shown. Varies by optic and CCT. Consult specification sheets for more detailed information.

	WDGE LED Wall-Mount				ARC LED Wall-Mount	
						
	WDGE1 LED	WDGE2 LED	WDGE3 LED	WDGE4 LED	ARC1 LED	ARC2 LED
Value Proposition in 30 Seconds	The WDGE family of LED wall-mounted luminaires uses four sizes, two optical technologies and one common shape to create a true site-wide solution with all the egress lighting and controls options specifiers demand.				Upgrade your expectations when you upgrade your wall-mounted lighting. The ARC LED family makes architectural styling and visually comfortable illumination affordable, meeting the needs of both new construction and renovation projects.	
PERFORMANCE						
Lumen Packages*	P1 - 1200 lumens, 10W P2 - 2000 lumens, 15W	P1 - 1200 lumens, 10W P2 - 2000 lumens, 15W P3 - 3,000 lumens, 23W P4 - 4,500 lumens, 35W P5 - 6,000 lumens, 48W	P1 - 7,500 lumens, 52W P2 - 8,500 lumens, 59W P3 - 10,000 lumens, 71W P4 - 12,000 lumens, 88W	P1 - 12,000 lumens, 77W P2 - 16,000 lumens, 106W P3 - 18,000 lumens, 123W P4 - 20,000 lumens, 140W P5 - 22,000 lumens, 156W P6 - 25,000 lumens, 185W	P1 - 1,500 lumens, 11W P2 - 2,000 lumens, 17W P3 - 3,000 lumens, 25W	P1 - 1,500 lumens, 11W P2 - 2,000 lumens, 16W P3 - 3,000 lumens, 24W P4 - 4,000 lumens, 30W P5 - 6,500 lumens, 51W
Voltage	MVOLT (120 - 277V) 347V	MVOLT (120 - 277V) 347V 480V			MVOLT (120 - 277V) 347V	
CORRELATED COLOR TEMPERATURE/COLOR RENDERING INDEX						
CCTs	2700K / 80 CRI 3000K / 80 CRI 3500K / 80 CRI 4000K / 80 CRI 5000K / 80 CRI (90 CRI also available)		3000K / 80 CRI 4000K / 80 CRI 5000K / 80 CRI (70 CRI also available)		3000K / 80 CRI 4000K / 80 CRI 5000K / 80 CRI	
CRI						
OPTIONAL CONTROLS & PATH OF EGRESS						
Motion Sensor	-	High/Low Motion Sensor with Integral Photocell (using nLight AIR)			-	
nLight® AIR	-	Yes	Yes	Yes	-	
Emergency Back Up	4W/0C	4W / 0C 10W / 5C 18W / -20C	15W / 5C 18W / -20C	-	4W/0C	4W/0C 8W / -20C
SERVICE PROGRAMS						
Design Select or Contractor Select					-	-

*Nominal lumens shown. Varies by optic and CCT. Consult specification sheets for more detailed information.

	WPX LED Wall-Mount				TWR/TWS Wall Packs		
							
	WPX0 LED	WPX1 LED	WPX2 LED	WPX3 LED	TWR1 LED	TWR2 LED	TWS LED
Value Proposition in 30 Seconds	WPX0 features four adjustable lumen outputs, three switchable color temperatures, and a switchable dusk-to-dawn photocell providing 24 configurations in one SKU!	The WPX family provides a complete wall-mounted lighting solution, from over-the-door lighting to perimeter lighting with mounting heights of up to 20 feet. The WPX LED wall pack lights deliver a wide photometric distribution that reduces the number of luminaires required while creating a well-illuminated nighttime environment.			The TWR and TWS LED wall packs offer the traditional shape you've grown accustomed to, coupled with the technology you need. Featuring adjustable lumen output, color switching and a switchable photocell, TWR and TWS provide 18 configurations in one product!		
PERFORMANCE							
Lumen Packages*	ALO: 850 - 1,650 lumens 6W - 13W	P1 - 3,250 lumens, 23W P2 - 4,400 lumens, 32W P3 - 5,250 lumens, 39W P4 - 6,850 lumens, 54W ALO - 1,450 - 6,850 lumens 9 - 54W	6,000 lumens, 47W	9,200 lumens, 69W	ALO: 2,300 lumens 5,300 lumens 8,500 lumens 16W - 59W	ALO: 8,200 lumens 12,100 lumens 16,100 lumens 55W - 112W	ALO: 1,000 lumens 1,700 lumens 2,400 lumens 7W - 17W
Voltage	MVOLT (120 – 277V)	MVOLT (120 – 277V) 347V			120-347V		MVOLT (120 – 277V)
CORRELATED COLOR TEMPERATURE/COLOR RENDERING INDEX							
CCTs	Switchable CCT: 3000K 4000K 5000K	3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI			Switchable CCT: 3000K 4000K 5000K		Switchable CCT: 3000K 4000K 5000K
CRI	70 CRI				80 CRI		80 CRI
OPTIONAL CONTROLS & PATH OF EGRESS							
Motion Sensor	Switchable Photocell	-			Switchable Photocell		Switchable Photocell
nLight® AIR	-	-			--		-
Emergency Back Up	-	4W / 0C, 14W / -20C		-	-		-
SERVICE PROGRAMS							
Design Select or Contractor Select				N/A			

*Nominal lumens shown. Varies by optic and CCT. Consult specification sheets for more detailed information.

	TWX LED (Glass) Wall-Mount			TWPX LED (Polycarbonate) Wall-Mount		
						
	TWX 1 LED	TWX2 LED	TWX3 LED	TWPX1 LED	TWPX2 LED	TWPX3 LED
Value Proposition in 30 Seconds	The TWX LED family of glass wall packs provide traditional styling with superior illumination and fast pay-back.			The vandal-resistant TWPX LED features a polycarbonate lens, making it ideal for low mounting height applications in high-traffic areas.		
PERFORMANCE						
Lumen Packages*	P1 - 1,600 lumens, 11W P2 - 2,950 lumens, 22W ALO - 600 - 2,950 lumens, 4 - 22W	P1 - 3,250 lumens, 23W P2 - 4,400 lumens, 32W P3 - 5,250 lumens, 39W P4 - 6,850 lumens, 54W ALO - 22,000 lumens, 9 - 54W	P1 - 8,800 lumens, 65W P2 - 10,650 lumens, 79 W P3 - 12,900 lumens, 97W P4 - 13,850 lumens, 108W ALO - 2,900 - 13,850 lumens, 18 - 108W	P1 - 1,450 lumens, 11W P2 - 2,700 lumens, 22W ALO - 550 - 2,700 lumens, 4 - 22W	P1 - 3,150 lumens, 23W P2 - 4,250 lumens, 32W P3 - 5,050 lumens, 39W P4 - 6,600 lumens, 54W ALO - 1,400 - 6,600 lumens, 9 - 54W	P1 - 8,400 lumens, 65W P2 - 10,150 lumens, 79W P3 - 12,300 lumens, 97W P4 - 13,200 lumens, 108W ALO - 2,750 - 13,200 lumens, 18 - 108W
Voltage	MVOLT (120 – 277V)	MVOLT (120 – 277V) 347V 480V	MVOLT (120 – 277V) 347V	MVOLT (120 – 277V)	MVOLT (120 – 277V) 347V 480V	MVOLT (120 – 277V) 347V
CORRELATED COLOR TEMPERATURE/COLOR RENDERING INDEX						
CCTs	3000K / 80 CRI 4000K / 80 CRI 5000K / 80 CRI					
CRI						
OPTIONAL CONTROLS & PATH OF EGRESS						
Motion Sensor	-			-		
nLight® AIR	-			-		
Emergency Back Up	-			-		
SERVICE PROGRAMS						
Design Select or Contractor Select						


*Nominal lumens shown. Varies by optic and CCT. Consult specification sheets for more detailed information.

D-Series LED Floodlighting				RSXF LED Floodlighting									
													
DSXF1 LED		DSXF2 LED		DSXF3 LED		RSXF1 LED		RSXF2 LED		RSXF3 LED		RSXF4 LED	
Value Proposition in 30 Seconds		The D-Series LED flood family is designed to meet the floodlight needs of specifiers while keeping the project on budget. With three sizes, seven different optics, a wide selection of mounting options and accessories, and lumen packages from 2,700 to 26,000, the D-Series LED flood family can be configured to meet the needs of any floodlighting application.						The RSX LED floodlighting luminaires are a complete solution for both renovation and new construction applications where value, an extensive range of options and industry-leading delivery are required.					
PERFORMANCE													
Lumen Packages*		P1 - 2,700 lumens, 21W P2 - 5,000 lumens, 42W		P1 - 7,000L lumens, 52W P2 - 10,000 lumens, 15W P3 - 12,000 lumens, 23W P4 - 17,000 lumens, 145W		P1 - 12,000 lumens, 111W P2 - 20,000 lumens, 138W P3 - 23,000 lumens, 23W P4 - 4,500 lumens, 35W P5 - 6,000 lumens, 48W		P1 - 1200 lumens, 10W P2 - 2000 lumens, 15W P3 - 3,000 lumens, 23W P4 - 4,500 lumens, 35W P5 - 6,000 lumens, 48W		P1 - 1200 lumens, 10W P2 - 2000 lumens, 15W P3 - 3,000 lumens, 23W P4 - 4,500 lumens, 35W P5 - 6,000 lumens, 48W		P1 - 1200 lumens, 10W P2 - 2000 lumens, 15W P3 - 3,000 lumens, 23W P4 - 4,500 lumens, 35W P5 - 6,000 lumens, 48W	
Voltage		MVOLT (120 – 277V) 347V		MVOLT (120-277V) 347V 480V		MVOLT (120 – 277V) HVOLT (347 – 480V) XVOLT (277 – 480V)		MVOLT (120 – 277V) HVOLT (347 – 480V) XVOLT (277 – 480V)		MVOLT (120 – 277V) HVOLT (347 – 480V) XVOLT (277 – 480V)		MVOLT (120 – 277V) HVOLT (347 – 480V) XVOLT (277 – 480V)	
CORRELATED COLOR TEMPERATURE/COLOR RENDERING INDEX													
CCTs		3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI						3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI		3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI		3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI	
CRI													
OPTIONAL CONTROLS & PATH OF EGRESS													
Motion Sensor		-		-		High / Low Motion Sensor with Integral Photocell (using nLight AIR)		High / Low Motion Sensor with Integral Photocell (using nLight AIR)					
nLight® AIR		-		-		Yes		Yes					
Emergency Back Up		-		-		-		-		-		-	
SERVICE PROGRAMS													
Design Select or Contractor Select		N/A		N/A		N/A							
													

*Nominal lumens shown. Varies by optic and CCT. Consult specification sheets for more detailed information.

	ESXF LED Floodlight Family						HLF LED High Lumen Floodlighting	
								
	ESXF1 PO LED	ESXF1 LED	ESXF2 LED	ESXF3 LED	ESXF4 LED	ESXF5 LED	HLF1 LED	HLF2 LED
Value Proposition in 30 Seconds	ESXF1 P0 delivers superior illumination and color switching.	ESXF LED is an all-in-one flood that gives ultimate versatility by offering 36 configurations in one product while delivering superior illumination and offering easy access to controls for color switching, adjustable lumens, and selectable photocell.					Capable of delivering over 100,000 lumens, the HLF is ideal for challenging lighting applications. In addition to flood optics, the HLF features hybrid silicone optics that create narrow distributions for spotlighting applications.	
PERFORMANCE								
Lumen Packages*	2,500 lumens	ALO: 1,500 lumens 3,000 lumens 5,000 lumens 9W - 34W	ALO: 3,500 lumens 5,500 lumens 7,500 lumens 22W - 56W	ALO: 8,500 lumens 10,500 lumens 14,000 lumens 53W - 100W	ALO: 16,000 lumens 18,000 lumens 20,000 lumens 111W - 150W	ALO: 30,000 lumens 40,000 lumens 50,000 lumens 177W - 341W	P1 - 24,000L, 163W P2 - 29,000L, 203W P3 - 38,000L, 289W P4 - 43,000L, 342W P5 - 50,000L, 368W	P1 - 1200 lumens, 10W P2 - 2000 lumens, 15W P3 - 3,000 lumens, 23W P4 - 4,500 lumens, 35W P5 - 6,000 lumens, 48W
Voltage	MVOLT (120 - 277V)			MVOLT (120-277V) UVOLT (120-347V)		UVOLT (120-347V) XVOLT (277-480V)	MVOLT (120 – 277V) HVOLT (347 – 480V)	
CORRELATED COLOR TEMPERATURE/COLOR RENDERING INDEX								
CCTs	Switchable CCT: 3000K - 4000K - 5000K 80 CRI						3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI	
CRI								
OPTIONAL CONTROLS & PATH OF EGRESS								
Motion Sensor	Switchable Photocell						-	
nLight® AIR	-						-	
Emergency Back Up	-						-	
SERVICE PROGRAMS								
Design Select or Contractor Select							N/A	N/A

*Nominal lumens shown. Varies by optic and CCT. Consult specification sheets for more detailed information.

	VCPG LED Parking Garage		VCVL LED	D-Series Parking		Canopy Luminaires		
								
	VCPG	VCPGX	VCVL	DSXPG	DSXPGT	CNY ALO	PCNY	SCNY
Value Proposition in 30 Seconds	The VCPG LED brings visual comfort, energy efficiency and style to parking garage applications. The VCPGX provides the ultimate in visual comfort with a recessed lens and patented transition zone. Increase energy savings and gain code- compliance with the addition of nLight AIR controls.		The VCVL LED is designed to bring glare control, optical performance and energy savings into one package. The recessed lens design of VCVL LED minimizes high angle glare, while its precision molded acrylic lens eliminates LED pixilation and delivers uniform distribution. The dedicated up-light module option reduces the contrast between the luminaire and the ceiling creating a more visually comfortable environment.	The D-Series Parking Garage luminaires combine the known benefits of LED with a versatile and highly configurable solution while delivering uniform optical performance. Our superior design leads to a better pedestrian and driver experience plus sizable energy savings resulting in a quick payback period.		With an incredible 54 customizable options packed into a single luminaire, you have the power to tailor your lighting experience right on the spot. Adjust color temperature, lumen output photocell settings, and even activate the integrated motion sensor.	Experience exceptional energy savings, powerful performance and versatility with the PCNY LED Canopy. Designed with three adjustable lumen outputs to ensure ample lighting for customer safety and visibility. Available with three lens options, the PCNY can be customized for visual preference.	Designed with three adjustable lumen outputs to ensure ample lighting for customer traffic in and out of retail applications. Available with four lens options, the SCNY can be customized for any visual preference.
PERFORMANCE								
Lumen Packages*	P1 - 3,700 lumens, 27W P2 - 4,700 lumens, 34W P3 - 6,000 lumens, 43W P4 - 7,500 lumens, 56W P5 - 10,000 lumens, 82W P6 - 13,000 lumens, 108W P7 - 16,000 lumens, 122W		P1 - 3,700 lumens, 27W P2 - 4,700 lumens, 34W P3 - 6,000 lumens, 43W P4 - 7,500 lumens, 56W P5 - 10,000 lumens, 82W P6 - 13,000 lumens, 108W P7 - 16,000 lumens, 122W	Multiple options available: 2,600 – 11,000L 25W - 107W	Multiple options available: 8,600 – 22,000L 74W - 214W	ALO: 5,000 lumens 7,500 lumens 10,000 lumens 34W - 75W	ALO: 7,500 lumens 10,000 lumens 13,000 lumens 46W - 84W	P1 - 4,200 lumens ALO - 7,500, 10,000, 13,000 lumens 28W - 84W
Voltage	MVOLT (120 - 277V) (347V - 480V)			MVOLT (120 - 277V) (347V - 480V)		MVOLT (120 - 277V) UVOLT (120-347V)	MVOLT (120 - 277V) HVOLT (347 - 480V)	
CORRELATED COLOR TEMPERATURE/COLOR RENDERING INDEX								
CCTs	3000K / 70 or 80 CRI 3500K / 70 or 80 CRI 4000K / 70 or 80 CRI 5000K / 70 or 80 CRI			3000K / 80 CRI 4000K / 70 CRI 5000K / 65 CRI		Switchable CCT: 3000K-4000K-5000K	Switchable CCT: 3000K-4000K-5000K	
CRI						80 CRI	70 CRI	
OPTIONAL CONTROLS & PATH OF EGRESS								
Motion Sensor	High/Low Motion Sensor with Integral Photocell		High/Low Motion Sensor with Integral Photocell	Motion / Ambient Sensor / Photocell		Standard Selectable Motion: On/Off/10% Dim with Integral Photocell	-	-
nLight® AIR	Yes		Yes	-		-	-	-
Emergency Back Up	8W / -20C 10W / 5C		8W / -20C 10W / 5C	-		-	-	-
SERVICE PROGRAMS								
Design Select or Contractor Select	N/A	N/A	N/A	N/A	N/A		N/A	N/A

*Nominal lumens shown. Varies by optic and CCT. Consult specification sheets for more detailed information.

	RADEAN	D-Series LED	KB Series			
	 RADB	 DSXB	 KBA8	 KBC8	 KBD8	 KBR8
Value Proposition in 30 Seconds	The Radean LED bollard is the ideal companion to the Radean area luminaires for pedestrian spaces	The D-Series LED bollard combines modern styling and durable construction making it ideal for public spaces.	The KB LED bollard's contemporary styling and energy efficiency makes it the right choice for replacing aging HID bollards and is ideal for illuminating building entryways, walking paths, and pedestrian plazas.			
PERFORMANCE						
Lumen Packages*	P1 - 400 lumens, 5W P2 - 700 lumens, 8W P3 - 1,150 lumens, 13W P4 - 1,600 lumens, 19W P5 - 2,550 lumens, 32W	350 - 1,700 lumens, 20W 530 - 2,400 lumens, 28W 700 - 3,000 lumens, 39W	350 - 1,650 lumens, 20W 530 - 2,350 lumens, 28W 700 - 2,950 lumens, 39W	350 - 1,100 lumens, 20W 530 - 1,600 lumens, 28W 700 - 2,000 lumens, 39W		
Voltage	MVOLT (120 – 277V) 347V	MVOLT (120 – 277V) 347V	MVOLT (120 – 277V) 347V			
CORRELATED COLOR TEMPERATURE/COLOR RENDERING INDEX						
CCTs	2700K / 70 CRI 3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI	3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI PC Amber LW Amber	3000K / 70 CRI 4000K / 70 CRI 5000K / 70 CRI PC Amber LW Amber			
CRI						
OPTIONAL CONTROLS & PATH OF EGRESS						
Motion Sensor	Yes	-	-			
nLight® AIR	-	-	-			
Emergency Back Up	7W/0C	23W/-20C	23W/-20C			

*Nominal lumens shown. Varies by optic and CCT. Consult specification sheets for more detailed information.

	BarnGuard LED	HomeGuard (HGX) LED						
								
	BarnGuard (BGR)	HGX 2RH 40K	HGX 2RH ALO 40K PE	HGX 2RH ALO SWW2 PE	HGX 2SH ALO SWW2 PE	HGX 3RH ALO SWW2 PE	HGX 2RH ALO SWW2 PIR	HGX 2RH 40K MO
Value Proposition in 30 Seconds	The BarnGuard LED is an energy-efficient, long-lasting, cost-effective replacement for HID security fixtures.	The HomeGuard LED family of residential security lights are long-lasting, energy-efficient solutions for replacing incandescent PAR lamp fixtures. Mounted on the wall or under the eaves, these luminaires provide reliable safety and security lighting in residential applications. HomeGuard LED security lights are available with the right feature sets for every application; ranging from a low-cost version for switched circuit applications to a fully featured product with an integral photocell for automatic dusk-to-dawn lighting, color-switching, lumen switching and a motion sensor. Easy to install and experience, HomeGuard LED floodlights are the best choice for contractors and DIY customers alike.						
PERFORMANCE								
Lumen Packages*	ALO: 6,000 lumens 10,000 lumens	2,750 lumens	ALO: 1,750 lumens 2,750 lumens	ALO: 1,800 lumens 2,750 lumens	ALO: 1,700 lumens 2,700 lumens	ALO: 1,750 lumens 2,750 lumens 4,100 lumens	ALO: 2,150 lumens 2,600 lumens	2,750 lumens
Voltage	MVOLT (120 - 277V)	120V		120V				120V
CORRELATED COLOR TEMPERATURE/COLOR RENDERING INDEX								
CCTs	Switchable CCT: 3000K/4000K/5000K	4000K / 80 CRI		Switchable CCT: 3000K/4000K/5000K 80 CRI				4000K / 80 CRI
CRI								
OPTIONAL CONTROLS & PATH OF EGRESS								
Motion Sensor	Twist-Lock Photocell	Photocell					PIR Motion Sensor	Motion Sensor
nLight® AIR	-	-	-	-	-	-	-	-
Emergency Back Up	-	-	-	-	-	-	-	-
SERVICE PROGRAMS								
Design Select or Contractor Select					N/A			